

March 15, 2022



## FUNCTIONAL SERVICING REPORT

### PROPOSED COLUMBIA SQUARE MIXED-USE DEVELOPMENT

14245 HIGHWAY 50  
TOWN OF CALEDON, REGION OF PEEL

Project No.: 21-0012CA

January 2022



## **Table of Contents**

|  | <b><u>PAGE</u></b> |
|--|--------------------|
| <b>1.0 INTRODUCTION .....</b>                      | <b>1</b>           |
| 1.1 Study Objectives and Location.....             | 1                  |
| 1.2 Existing Condition .....                       | 1                  |
| 1.3 Proposed Development.....                      | 2                  |
| 1.4 References.....                                | 4                  |
| <b>2.0 STORMWATER MANAGEMENT.....</b>              | <b>5</b>           |
| 2.1 Existing Conditions.....                       | 5                  |
| 2.1.1 Topography and Drainage .....                | 5                  |
| 2.1.2 Existing Storm Drainage Infrastructure ..... | 6                  |
| 2.1.3 Soil Conditions .....                        | 6                  |
| 2.2 Stormwater Design Criteria .....               | 8                  |
| 2.3 Proposed Stormwater Management .....           | 9                  |
| 2.3.1 Quantity control.....                        | 9                  |
| 2.3.2 Quality Control .....                        | 12                 |
| 2.3.3 Site Grading and Drainage .....              | 12                 |
| 2.3.4 Water Balance .....                          | 12                 |
| <b>3.0 SANITARY SERVICING.....</b>                 | <b>14</b>          |
| 3.1 Existing Sanitary Infrastructure .....         | 14                 |
| 3.2 Design Criteria .....                          | 14                 |
| 3.3 Proposed Sanitary servicing .....              | 14                 |
| <b>4.0 Water Supply Servicing.....</b>             | <b>16</b>          |
| 4.1 Existing Water Supply Infrastructure .....     | 16                 |
| 4.2 Design Criteria .....                          | 16                 |
| 4.3 Proposed Water Supply Servicing .....          | 17                 |
| <b>5.0 SUMMARY .....</b>                           | <b>18</b>          |



## **List of Tables**

|   | <b><u>PAGE</u></b> |
|---|--------------------|
| Table 1-1: Anticipated Design Population .....                              | 2                  |
| Table 2-1: Pre-Development Peak Flow Summary .....                          | 5                  |
| Table 2-2: Rainfall Intensity Equation Coefficients .....                   | 8                  |
| Table 2-3: Summary of Allowable Release Rates .....                         | 10                 |
| Table 2-4: Summary of Storage Requirements .....                            | 10                 |
| Table 2-5: Summary of Water Balance Mitigation Retention Requirements ..... | 13                 |
| Table 3-1: Summary of Anticipated Sanitary Flows .....                      | 15                 |
| Table 4-1: Preliminary Water Demands .....                                  | 17                 |

## **List of Figures**

|  | <b><u>PAGE</u></b> |
|--|--------------------|
| Figure 1-1: Site Location Plan .....     | 3                  |
| Figure 2-1: Existing Drainage Plan ..... | 7                  |
| Figure 2-2: Proposed Drainage Plan ..... | 11                 |

## **Appendices**

- Appendix A: Proposed Site Plan
- Appendix B: Background Information
- Appendix C: Stormwater Management Calculations
- Appendix D: Sanitary Calculations
- Appendix E: Water Supply Calculations
- Appendix F: Functional Servicing Drawings



## **1.0 INTRODUCTION**

### **1.1 Study Objectives and Location**

This Functional Servicing Report has been prepared in support of a proposed Official Plan Amendment (OPA) and Zoning By-Law Amendment (ZBA) for lands located northeast of the Columbia Way and Highway 50 intersection, in the Town of Caledon, Regional Municipality of Peel. The civic address of the subject property is 14245 Highway 50. The site is proposed to be developed in four phases (1A, 1B, 2, and 3), which include residential and commercial land uses.

The overall site can be legally described as Part 2 of Plan 43R-38843, Town of Caledon (Settlement Area of Bolton), Regional Municipality of Peel. The subject property is located within the boundaries of Castlederg Sideroad to the north, Highway 50 to the west, Mount Hope Road to the east and Columbia Way to the south. The site is within the jurisdiction of the Toronto and Region Conservation Authority (TRCA). A Site location plan is provided in Figure 1-1.

The following report provides information regarding site servicing and stormwater management for the subject development while ensuring compatibility with services already in place. The report will also address comments raised by regulatory agencies (i.e., Region of Peel, Town of Caledon and TRCA).

### **1.2 Existing Condition**

The site is irregular in shape with an area of approximately 3.3 ha. Currently the site is vacant and appears to be used for agricultural purposes. To the east of the site is an existing school (St. Michael Catholic Secondary School). To the south is Kingsview Drive, and a residential development opposite Columbia Way, to the west is a Town Works Yard opposite Highway 50, and to the north is vacant/agricultural land. There appears to be four driveway entrances to the site: three along Columbia Way and one along Highway 50.

The subject site was included in the design of the infrastructure for the existing residential subdivision south of Columbia Way. Previous designs considered the site as part of a 5.3 ha commercial area. This suggests that for a 3.30 ha parcel of commercial land, the intended population for the site that was included in the design of existing infrastructure is approximately 165 people (50 people per hectare \* 3.30 ha = 165 people).



### 1.3 Proposed Development

The subject development of approximately 3.30 hectares, located in the community of Bolton and is municipally addressed as 14245 Highway 50, Caledon, Ontario. The subject site is subdivided into four phases (1A, 1B, 2 and 3). Phases 1A and B, located on the north portion of the site, is proposed to contain three and six townhouse blocks, respectively, with private laneways and on-grade parking. Phase 2, located on the southwest corner of the site, is proposed to contain a plaza with two mixed-use buildings (ground floor commercial podium with residential on upper floors), amenity areas, and parking facilities (both on-grade and below ground). Phase 3, located on the southeast corner of the site, is proposed to contain a retirement residence and parking facilities (both on-grade and below ground).

Two private roadways are proposed through the subject site to provide vehicular access between blocks and phases. A primary vehicular access is proposed on Columbia Way, approximately 100 metres east of Highway 50. A secondary vehicular access is proposed on Highway 50, approximately 150 metres north of Columbia Way. A proposed site plan is provided in Appendix A.

The anticipated design population is as summarized in Table 1-1 and was determined using Region of Peel design criteria.


**Table 1-1: Anticipated Design Population**

| Description                           | Units | Area (ha) | Population |
|---------------------------------------|-------|-----------|------------|
| Phase 1A – Townhouse Units            | 24    | 0.72*     | 126        |
| Phase 1B – Townhouse Units            | 118   | 0.68      | 119        |
| Phase 2 – Mixed-Use Comm./Residential | 244   | 1.29      | 613        |
| Phase 3 – Retirement Residence        | 159   | 0.61      | 290        |
| Total                                 | 545   | 3.30      | 1,148      |

\* Includes 0.22 ha laneway







**urbanworks**  
ENGINEERING CORPORATION  
Toronto, Ontario, Canada | tel. 416-503-4500  
e. general@urbanworkseng.com | w. www.urbanworkseng.com

#### LEGEND

SITE LOCATION

FIGURE 1-1

SITE LOCATION PLAN  
COLUMBIA SQUARE  
CALEDON, ON.

21-0012CA

JANUARY 2022

SCALE: N.T.S.

## 1.4 References

The following material has been reviewed during the preparation of this report:

- **A & A environmental Consultants Inc.**, *Geotechnical Engineering Report, Residential property Located at 14245 Highway 50, Caledon, Ontario*, October 26, 2021.
- **A & A environmental Consultants Inc.**, *Small Scale Hydrogeological Assessment, Residential property Located at 14245 Highway 50, Caledon, Ontario*, November 4, 2021.
- **Aecom**, *Engineering Drawings*, dated June 2012.
- **Anton Kikas Limited**, *Engineering drawings*, dated February 1992.
- **KFA Architects and Planners**, *Phase 1-3 Columbia Square Combined Site Plan*, dated July 20, 2021.
- **MMM Group**, *Servicing Investigation Letter, Bolton secondary School, Town of Caledon, File No: 10-06629*, dated July 13, 2006.
- **MMM Group**, *Site Servicing Plan, St. Michael Secondary School*, dated November 2008.
- **R-PE Surveying Ltd.**, *Topographic Survey*, dated July 13, 2021.
- **Region of Peel – Public Works Water and Wastewater Program Planning**, *Bolton Residential Expansion, Analysis in Support of the Regional Official Plan Amendment*, dated June 8, 2016.
- **Region of Peel**, *Public Works Design, Specifications & Procedures Manual*, dated March 2017.
- **Town of Caledon**, *Site Plan Control Manual: Submission Package*, August 2019.
- **Town of Caledon**, *Development Standards Manual, Version 5.0*, 2019.
- **Toronto and Region Conservation Authority**, *Stormwater Management Criteria*, August 2012.
- **Toronto and Region Conservation Authority / Credit Valley Conservation**, *Low Impact Development Stormwater Management Planning and Design Guide*, 2010.



## 2.0 STORMWATER MANAGEMENT

### 2.1 Existing Conditions

#### 2.1.1 Topography and Drainage

Review of existing site conditions was carried out using a topographical survey. The topographical information was obtained from a detailed survey completed by R-OE Surveying Ltd., in July 2021.

The subject site is located within the Humber River Watershed, as illustrated in the 2012 TRCA Stormwater Management Criteria. The site is located in an area where quantity flood control is not required. On-site controls may still be required depending on the available infrastructure.

The site generally drains in a southerly direction towards the intersection of Columbia Way and Highway 50. The elevation range on site varies from 269.5 at the northeast corner, to 259.9 at the southwest corner. This suggests a topographic range of approximately 9.6 m. Figure 2-1 provides an illustration of the existing drainage conditions.

Existing peak flows from the site were estimated using the Rational Method. The time of concentration was determined using the Bransby Williams Method. Table 2-1 provides a summary of the pre-development peak flows for the site. The flows are based on an area of 3.30 ha and runoff coefficient of 0.25. Calculations are provided in Appendix C.

**Table 2-1: Pre-Development Peak Flow Summary**

| Storm Event | Peak Flow<br>(m <sup>3</sup> /s) |
|-------------|----------------------------------|
| 2-yr        | 0.106                            |
| 5-yr        | 0.145                            |
| 10-yr       | 0.178                            |
| 25-yr       | 0.215                            |
| 50-yr       | 0.244                            |
| 100-yr      | 0.274                            |





### 2.1.2 Existing Storm Drainage Infrastructure

Both Columbia Way and Highway 50 have rural cross-sections adjacent the site, meaning that runoff is conveyed via roadside ditches and culverts. The areas east, and south of Columbia Way have been developed, and therefore there is existing drainage infrastructure in the vicinity. Existing infrastructure includes:

- Two existing 350 mm diameter culverts along the north side of Columbia Way to convey flow westerly, beneath driveways.
- An existing 400 mm diameter culvert along the north side of Columbia Way to convey flow westerly underneath a driveway.
- An existing 1200 mm diameter culvert at the southwest corner of the site that conveys flow southerly beneath Columbia Way.
- An existing 1050 mm diameter storm sewer along Kingsview Drive, east of the site, which extends 1.5 m north of Columbia Way street-line.

The existing 1050 mm storm sewer was constructed with a slope of 0.36% (designed at 0.5%) and has a capacity of 1.709 m<sup>3</sup>/s. A report prepared by MMM indicates that this storm sewer was designed to accommodate 9.70 ha north of Columbia way, but this area was not delineated. Existing infrastructure is shown schematically in Figure 2-1.


There is an existing SWM Pond downstream of the site. The SWM Pond is located south of Columbia Way, between Taylorwood Avenue and St. Michael's Crescent. This pond provides water quantity and quality control for its respective catchment area.

### 2.1.3 Soil Conditions

A geotechnical investigation of the subsurface conditions of the subject property was carried out by A & A Environmental Consultants Inc. and the results of the investigation are provided in the October 2021 report.

The results of the investigation indicate that the soil stratigraphy of the site consists of a 0.0 m to 0.1 m layer of topsoil. Native material consists of deposits of silt & clay with trace gravel and/or sand across the site from 0.1 m to 13.5 m below grade. A clayey silt layer with some sand and trace gravel was found at depths of 13.5 m to 17.9 m below grade. Groundwater elevations ranged from 260.7 to 262.6 masl. The A & A study results will be used at the final design stage.






**urbanworks**  
ENGINEERING CORPORATION  
80 Jutland Road, Suite 500, Toronto, Ontario, M8Z 2H1  
e. general@urbanworkseng.com | w. www.urbanworkseng.com

#### LEGEND

- EXISTING STORM SEWER
- = EXISTING CULVERT
- EXISTING CONTOUR
- ➔ OVERLAND FLOW DIRECTION

AREA I.D.



RUNOFF  
COEFF.

DRAINAGE  
AREA

FIGURE 2-1  
EXISTING DRAINAGE PLAN  
COLUMBIA SQUARE

21-0012CA

JAN. 2022

SCALE: NTS

## 2.2 Stormwater Design Criteria

Stormwater management design criteria for the proposed development were established through a review of regulatory agency design standards, along with background design information for the existing subdivision and stormwater management pond. The relevant stormwater management guidelines are listed below.

### Town of Caledon Criteria:

- Local storm sewers shall be designed using the Rational Method and based on a 5-year storm return frequency:

$$Q = C i A / 360$$

Where: Q = Flow Rate (m<sup>3</sup>/s)  
C = Runoff Coefficient  
i = Rainfall Intensity (mm/hr)  
A = Drainage Area (ha)

- Rainfall Intensity calculations for storm sewer design will be based on the Town of Caledon standard IDF relationships, and will be calculated as follows:

$$i = A / (t_c + B)^C$$

Where: A, B, C are constants per Table 2-1 below  
t<sub>c</sub> = Time of Concentration (min.), with a minimum time of 10 min.

**Table 2-2: Rainfall Intensity Equation Coefficients**

| Storm Event | Coefficients |      |        |
|-------------|--------------|------|--------|
|             | A            | B    | C      |
| 2-year      | 1070         | 7.85 | 0.8759 |
| 5-year      | 1593         | 11   | 0.8789 |
| 10-year     | 2221         | 12   | 0.9080 |
| 25-year     | 3158         | 15   | 0.9335 |
| 50-year     | 3886         | 16   | 0.9495 |
| 100-year    | 4688         | 17   | 0.9624 |

- Acceptable flow velocities within storm sewer shall be between 0.75m/s and 4.0m/s for



pipes flowing full. Super-critical flows will not be accepted.

- Minimum pipe slope shall be 0.40% (unless adequate self-cleansing velocity is confirmed).
- Minimum pipe size for storm sewer main lines is 300 mm.

#### TRCA Criteria:

- Enhanced (Level 1) water quality protection (80% TSS removal).
- Minimum retention of the first 5 mm of rainfall for water balance and erosion control.

## **2.3 Proposed Stormwater Management**

The proposed stormwater management system has been designed in accordance with Town of Caledon and TRCA guidelines. The intent of the design is to ensure conformance with the overall stormwater management plan for the area and ensure no negative impacts to adjacent properties and infrastructure. A stormwater management plan is required to address mitigation measures with respect to quantity control, quality control, erosion control and water balance. In general, the proposed stormwater management system will use on-site controls in accordance with the design of existing infrastructure.

It is noted that the site will be developed in phases. While this FSR demonstrates the serviceability of all phases, each phase will require a SWM report during the detailed design stages of the project.

### **2.3.1 Quantity control**

The site is in a sub-watershed that does not require quantity controls; however it is proposed to reduce peak flows to protect existing infrastructure from being overwhelmed. To be consistent with adjacent SWM designs, it is proposed to control peak flows to 180 L/s/ha. Therefore, the allowable release rate for the entire site is 0.594 m<sup>3</sup>/s (180 L/s/ha \* 3.30 ha / 1000 L/m<sup>3</sup> = 0.594 m<sup>3</sup>/s).

The site is proposed to be developed in stages and therefore allowable release rates were determined for each phase. This will allow each phase to have its own flow controls and storage requirement. The allowable release rates are as summarized in Table 2-3 and account for uncontrolled flow areas (Area 4 in Figure 2-2). There is approximately 0.22 ha of uncontrolled area, generating a peak flow of 108 L/s during a 100-year storm.



100-yr Storage volumes for each Phase were calculated using the Rational Method. Storage requirements for each phase are summarized in Table 2-4. Calculations are provided in Appendix C.

**Table 2-3: Summary of Allowable Release Rates**

| Phase | Area (ha) | Allowable Release Rate* (L/s) |
|-------|-----------|-------------------------------|
| 1A    | 0.50      | 78.9                          |
| 1B    | 0.68      | 107.3                         |
| 2     | 1.29      | 203.5                         |
| 3     | 0.61      | 96.2                          |
| 4     | 0.22      | 108.1*                        |
| Total | 3.30      | 594.0                         |

\* Indicates uncontrolled flow


**Table 2-4: Summary of Storage Requirements**

| Phase No. | Area (ha) | Required Storage (m <sup>3</sup> /s) |
|-----------|-----------|--------------------------------------|
| 1A        | 0.72      | 123.0                                |
| 1B        | 0.68      | 167.3                                |
| 2         | 1.29      | 317.4                                |
| 3         | 0.61      | 150.1                                |
| 4         | 0.22      | NA                                   |
| Total     | 3.30      | 757.8                                |

NA – not applicable

Anticipated SWM tank and orifice locations are shown schematically on Figure 2-2. Additional details are provided on the Functional Engineering Drawings in Appendix F. Pipe and orifice sizes will be provided during the detailed design stage.





**urbanworks**  
ENGINEERING CORPORATION  
Toronto, Ontario, Canada | tel. 416-503-4500  
e. general@urbanworkseng.com | w. www.urbanworkseng.com

#### LEGEND

- EXISTING STORM SEWERS
- PROPOSED STORM SEWERS
- EXISTING SEWER TO BE REMOVED
- PROPOSED ORIFICE LOCATION
- OIL-GRIT SEPARATOR
- FULL-CAPTURE INLET
- UNCONTROLLED DRAINAGE AREA

| AREA I.D.  | 100   0.50<br>1.00ha | RUNOFF<br>COEFF.<br>DRAINAGE<br>AREA |
|--|----------------------|--------------------------------------|
| <span style="background-color: yellow;">■</span> | PHASE 1A             |                                      |
| <span style="background-color: orange;">■</span> | PHASE 1B             |                                      |
| <span style="background-color: blue;">■</span>   | PHASE 2              |                                      |
| <span style="background-color: purple;">■</span> | PHASE 3              |                                      |

PROPOSED SWM TANK

FIGURE 2-2  
PROPOSED DRAINAGE PLAN  
COLUMBIA SQUARE

21-0012CA

JAN. 2022

SCALE: NTS



As shown on the drawings, there are a couple of lengths of existing storm sewer that will need to be reconfigured to accommodate Phase 3. The storm sewers that will be realigned are currently servicing the adjacent school to the east and are located at the Kingsview Drive and Columbia Way intersection. The realignment will be address during the details design stage for Phase 3 and presented in a SWM Report.

### **2.3.2 Quality Control**

Water quality control is proposed using the existing SWM Pond located south of Columbia Way, between Taylorwood Avenue and St. Michael's Crescent. This pond was sized to provide 80% TSS removal for its catchment area.

In addition to the SWM Pond, an oil and grit separator (OGS) at the outlet of the site. More specifically a Stormceptor model EFO12 is proposed. The OGS unit was sized to provide 80% TSS removal. The Stormceptor sizing report is provided in Appendix C.

Despite being designed for 80% TSS removal, credit for 50% removal is generally given from conservation authorities and municipalities. The OGS should be considered as pre-treatment of runoff prior to discharging it into the existing system.

### **2.3.3 Site Grading and Drainage**

The grading design for the site was produced based on a topographic survey prepared by R-PE Surveying Ltd, dated July 2021. Existing elevations are proposed to be matched along all property lines, and in general the site will be graded for containment of runoff within the site boundaries. Proposed internal grades will be set to ensure that maximum surface ponding will not exceed 0.30m at catchbasin low points, in the event of total blockage of any storm inlet. Flows from storms up to the 100-year event are proposed to be contained within the site without overflow. For emergency situations (i.e., storms exceeding the 100-year event or failure of the internal drainage system), an over-land flow route has been established to ensure that surface flows will exit the site directly onto Columbia Way via the site entrances.

The proposed drainage scheme is illustrated in Figure 2-2. Preliminary grading plans are provided in Appendix F.

### **2.3.4 Water Balance**

A water balance analysis was prepared by A & A Consultants Inc. and presented in a hydrogeological report. Based on this analysis, an infiltration deficit of 4,569.7 m<sup>3</sup> per year was estimated as a result of the proposed development.



In accordance with TRCA criteria for sites less than 5 ha, it is proposed to retain 5 mm of rainfall on-site for every event to mitigate the infiltration deficit. As mentioned previously, the site is proposed to be developed in phases. Therefore, each phase will require a separate water balance mitigation strategy. For the purpose of water balance mitigation, Areas 1A and 4 will be combined. Retention volume requirements for each phase are provided in Table 2-5.

**Table 2-5: Summary of Water Balance Mitigation Retention Requirements**

| Phase | Area (ha) | Runoff Coefficient | Volume Required (m <sup>3</sup> ) |
|-------|-----------|--------------------|-----------------------------------|
| 1A    | 0.72*     | 0.90               | 32.4                              |
| 1B    | 0.68      | 0.90               | 30.6                              |
| 2     | 1.29      | 0.90               | 58.0                              |
| 3     | 0.61      | 0.90               | 27.5                              |
| Total | 3.30      | 0.90               | 148.5                             |

\* Includes 0.22 ha from Area 4

In Phase 1A it is proposed to utilize rear-yard infiltration trenches to retain 5 mm of rainfall. The proposed dimensions for the trench are 1.0 m wide, 1.0 m depth, and 118 m long. This suggests a retention volume of 47.1 m<sup>3</sup> ( $1.0 \text{ m} \times 1.0 \text{ m} \times 118 \text{ m} \times 0.4 \text{ porosity} = 47.2 \text{ m}^3$ ). The infiltration trench should be a minimum of 1.0 m above the high-water table. Infiltration testing should be completed in support of the detailed design of the infiltration trench.

The remainder of the site (Phases 1B, 2, and 3) will have an underground parking structure underneath, making infiltration-type LID measures infeasible. For this reason, it is proposed to provide additional storage in each SWM tank. The additional water stored in each tank will be used for irrigation or grey water uses (e.g. toilet flushes).



## 3.0 SANITARY SERVICING

### 3.1 Existing Sanitary Infrastructure

The development of the existing subdivision south of Columbia Way included the construction of an existing sanitary sewer system. A 250 mm diameter sanitary sewer is located along Kingsview drive and extends 1.5 m north of the Columbia Way ROW. Based on available servicing reports, this sanitary sewer was designed to accommodate the site with a commercial land use. A 3.3 ha site with commercial land use would have a design population of 165 people ( $3.30 \text{ ha} \times 50 \text{ p/ha} = 165 \text{ people}$ ).

### 3.2 Design Criteria

The sanitary sewer design and flow calculations are based on the following Region of Peel guidelines:

- Domestic sewage flow rate is 302.8 L/cap/day.
- Infiltration rate is 0.2 L/s/ha of gross area.
- Harmon Peaking Factor, K is  $1 + 14 / (4 + P^{0.5})$ , where P is population in thousands.
- Population density is based on Table 1-14 in the *Engineering Design Criteria & Standard Drawings*, dated 2013, which includes the following:
  - Apartments 475 persons/ha or 2.7 ppu
  - Commercial 75 persons/ha
  - Row Dwellings 175 persons/ha

### 3.3 Proposed Sanitary servicing

It is proposed to collect wastewater from each phase of the development, via a network of gravity sewers, and convey it to the existing sanitary sewer along Kingsview Drive. As mentioned previously, the existing system accounted for 3.30 ha of commercial area, with a design population of 165 people. Given that the proposed design population for the site is 1,148 people, an analysis will be required to confirm available capacity in the existing system to accommodate the additional population.

It is noted however, that the design population for Phase 1A is less than 165. Therefore, there should be available capacity to accommodate Phase 1A. The remaining phases can move



forward upon confirmation of available capacity. Anticipated flows from the site are provided in Table 3-1. Calculations are provided in Appendix D. Proposed sanitary servicing is shown in the Functional Servicing Plan provided in Appendix F.

**Table 3-1: Summary of Anticipated Sanitary Flows**

| Phase | Design population | Average Flow (L/s) | Peak Flow (L/s) | Infiltration Flow (L/s) | Total Flow (L/s) |
|-------|-------------------|--------------------|-----------------|-------------------------|------------------|
| 1A    | 126               | 0.4                | 1.5             | 0.1                     | 1.6              |
| 1B    | 119               | 0.4                | 1.5             | 0.3                     | 1.8              |
| 2     | 613               | 2.1                | 7.9             | 0.3                     | 8.2              |
| 3     | 290               | 1.0                | 3.8             | 0.1                     | 3.9              |
| Total | 1,148             | 3.9                | 14.7            | 0.8                     | 15.5             |

As shown on Dwg. FS-01, realignment of the existing sanitary sewer network at the Columbia Way and Kingsview drive intersection is required to accommodate Phase 3.



## 4.0 Water Supply Servicing

### 4.1 Existing Water Supply Infrastructure

The development of the existing subdivision south of Columbia Way included the construction of an existing watermain network. Existing watermains in the vicinity of the site include the following:

- 400 mm diameter PVC watermain along the south side of Columbia Way. This watermain extends from Highway 50 to an existing valve chamber east of Kingsview Drive.
- 400 mm diameter watermain along the east side of Kingsview Drive. This watermain extends 1.5 m north of the Columbia Way ROW.
- 400 mm diameter watermain along the east side of Highway 50 south of Columbia Way.

The existing water supply infrastructure is shown on the Functional Servicing Plan provided in Appendix F.

### 4.2 Design Criteria

The water demand used for watermain size selection should be equal to the Fire Flow Demand plus the Maximum Day Demand or the Maximum Hour Demand, whichever is greater. The following guidelines should be used in the design calculations for water supply as per Region of Peel's design criteria.

Typical Water Demand Criteria:

- Average Consumption Rate is:
  - 280 L/cap/day for residential areas
  - 300 L/cap/day for ICI areas
- Maximum Day Demand Factor is:
  - 2.0 for residential areas
  - 1.4 for ICI areas
- Peak Hour Demand Factor is 3.0
- Fire Protection demand calculated as per FUS



**Pressure:**

- Minimum pressure for Maximum Day and Fire Flow demand is 140 kPa (20 psi).
- Minimum pressure for Peak Hour demand is 275 kPa (40 psi).
- Maximum pressure under static loading is 690 kPa (100 psi).

### 4.3 Proposed Water Supply Servicing

The water distribution system for the proposed development will be designed in accordance with current Region of Peel standards. The proposed layout of the water distribution network for the development is shown on Drawing FS-01 – Functional Servicing Plan, included in Appendix F.

Drawing FS-01 illustrates the water distribution network together with other underground services, including proposed fire hydrant locations. The proposed internal network will generally consist of fire and domestic watermain. The sizes and locations of proposed watermain within the subject property will be verified at the time of detailed engineering design.

The preliminary water and fire flow demand analysis is summarized in Table 4-1. Calculations are included in Appendix E.

**Table 4-1: Preliminary Water Demands**

| Phase | Population | Average Day Demand (L/s) | Max. Day Demand (L/s) | Peak Hour Demand (L/s) | Fire Flow + Max. Day (L/s) |
|-------|------------|--------------------------|-----------------------|------------------------|----------------------------|
| 1A    | 126        | 0.4                      | 0.8                   | 1.2                    | 217.5                      |
| 1B    | 119        | 0.4                      | 0.8                   | 1.2                    | 150.8                      |
| 2     | 613        | 2.0                      | 4.0                   | 6.0                    | 254.0                      |
| 3     | 290        | 0.9                      | 1.9                   | 2.8                    | 118.5                      |
| Total | 1,148      | 3.7                      | 7.5                   | 11.2                   | 257.4                      |

As shown on Dwg. FS-01, realignment of existing watermain at the Columbia Way and Kingsview drive intersection is required to accommodate Phase 3.





## 5.0 SUMMARY

This report outlines the proposed servicing and stormwater management scheme for the proposed mixed-use development located at 14245 Highway 50, north of Columbia Way, in the Town of Caledon. The following is a summary of the conclusions and recommendations of this report:

### Stormwater Management

- Post-development peak flows are proposed to be controlled to 180 L/s/ha for storms up to, and including, the 100-year event. Flow control is proposed to be achieved using flow restrictors and a combination of underground pipe storage and storm chamber storage.
- Water quality control is provided by the Columbia Way SWM Pond. An OGS unit (EFO12) is proposed to provide pre-treatment for runoff prior to being discharged into the existing storm sewer system.
- Retention of 5mm of rainfall for water balance mitigation is proposed to be achieved through limited soil infiltration via rear-yard infiltration trenches in Phase 1A. Additional storage volume is proposed to be provided in the SWM tanks for re-use in Phases 1B, 2, and 3.
- Realignment of the existing storm sewers at the Kingsview Drive and Columbia Way intersection will be required to accommodate Phase 3.

### Sanitary Servicing

- Sanitary servicing is proposed via connection to the existing system along Kingsview Drive. There should be sufficient capacity available to service Phase 1A. Additional analysis is required prior to the remaining phases being constructed.
- Realignment of the existing sanitary sewers at the Kingsview Drive and Columbia Way intersection will be required to accommodate Phase 3.

### Water Supply Servicing

- Water supply servicing is proposed via connection to the existing 400 mm diameter watermain along Columbia Way.
- Realignment of existing watermains at the Kingsview Drive and Columbia Way intersection will be required to accommodate Phase 3.



Respectfully Submitted,

**Urbanworks Engineering Corporation**



**Michael Paulo, P.Eng.**  
Principal



---

## **Appendix A: Proposed Site Plan**

---

# COLUMBIA SQUARE


BOLTON, ONTARIO

© Copyright KFA Architects and Planners Inc., all rights reserved. No part of this document whether printed form or supplied as digital data may be reproduced, stored in a retrieval system or transmitted in any form or by any means, mechanical photocopying, recording or otherwise without the prior written permission of KFA Architects and Planners Inc.


All dimensions to be checked on site by the contractor. Drawings are not to be scaled, any discrepancies are to be reported to the Architect before proceeding with the work.

| No. | Description       | Date       |
|-----|-------------------|------------|
| 1   | ISSUED FOR REVIEW | 2021/07/12 |
| A   | ISSUED FOR REVIEW | 2021/07/20 |
|     |                   |            |
|     |                   |            |
|     |                   |            |
|     |                   |            |
|     |                   |            |
|     |                   |            |
|     |                   |            |

HALF SCALE  
DRAFT



PROJECT NORTH



STAMP

CLIENTS:

WYNDCLIFFE DEVELOPMENTS INC.



architects +  
planners inc.

PROJECT NO:

20065

SCALE:

1 : 500

DATE:

Issue Date

DRAWN BY:


RVW

DRAWING TITLE:

PHASE 1-3  
COMBINED SITE PLAN

DRAWING NO

SD002



| PHASES 1-3 - SITE AREA |         |      |      |          |      |            |
|------------------------|---------|------|------|----------|------|------------|
| m2                     | sq.ft   | FSI  | ha   | Units/ha | acre | Units/acre |
| 33013.27               | 355,352 | 1.67 | 3.30 | 165.1    | 8.16 | 66.8       |

| TOTAL PHASE 1 - SITE AREA |         |      |      |          |      |            |
|---------------------------|---------|------|------|----------|------|------------|
| m2                        | sq.ft   | FSI  | ha   | Units/ha | acre | Units/acre |
| 13728.14                  | 147,768 | 1.14 | 1.37 | 51.0     | 3.39 | 41.9       |

| PHASE 2 - SITE AREA |         |      |      |          |      |            |
|---------------------|---------|------|------|----------|------|------------|
| m2                  | sq.ft   | FSI  | ha   | Units/ha | arce | Units/acre |
| 13183.3             | 141,904 | 1.84 | 1.32 | 185.1    | 3.26 | 74.9       |

| PHASE 3 - SITE AREA |           |      |      |          |      |            |
|---------------------|-----------|------|------|----------|------|------------|
| m2                  | sq.ft     | FSI  | ha   | Units/ha | arce | Units/Acre |
| 6101.79             | 65,679.06 | 2.52 | 0.61 | 114.7    | 1.51 | 46.4       |

| SITE GROSS FLOOR AREA |                        |            |
|-----------------------|------------------------|------------|
| Phase 1               | GFA                    | 15586.0 m² |
|                       | Units                  | 142        |
|                       | Required Parking       | 261        |
|                       | Provided Parking       | 259        |
| Phase 2               | GFA                    | 24312.0 m² |
|                       | Units                  | 244        |
|                       | Required Parking       | 519        |
|                       | Provided Parking       | 471        |
| Phase 3               | GFA                    | 15365.0 m² |
|                       | Units                  | 159        |
|                       | Required Parking       | 278        |
|                       | Provided Parking       | 288        |
| Combined              | Total GFA              | 55263.0 m² |
|                       | Total Unit Count       | 545        |
|                       | Total Required Parking | 1057       |
|                       | Total Provided Parking | 1018       |

| GENERAL SITE STATISTICS      |         |
|------------------------------|---------|
| Gross Construction Area (m²) | 23,814  |
| Exclusions (m²)              | 8,228   |
| Gross Floor Area (m²)        | 15,586  |
| UNIT STATISTICS              |         |
| Total Number of Units        | 142     |
| Average Unit GFA (m2)        | 109.8   |
| Average Unit GFA (Sq.ft)     | 1,181.5 |
| PARKING                      |         |
| Required Parking             | 261     |
| Underground Parking          | 197     |
| Private Garage Parking       | 48      |
| Surface Parking              | 14      |
| Total Parking                | 259     |

| GENERAL SITE STATISTICS        |                     |
|--------------------------------|---------------------|
| Construction Area Total (m²)   | 37,755              |
| Parking Level GCA (m²)         | 11,838              |
| Condo Unit GCA (m²)            | 19,301              |
| Condo Amenity/Service GCA (m²) | 4,782               |
| Retail GCA (m²)                | 1,834               |
| Exclusions                     | 13,443              |
| Gross Floor Area (m2)          | 24,312              |
| UNIT STATISTICS                |                     |
| Total Number of Units          | 244                 |
| Average Unit GFA (m2)          | 79.1                |
| Average Unit GFA (Sq.ft)       | 851.5               |
| PARKING                        |                     |
| Required Retail Parking        | 1 Space/ 20 m² 92   |
| Required Residential Parking   | 1.5 Spaces/Unit 366 |
| Required Visitor Parking       | 0.25 Spaces/Unit 61 |
| Total Parking Required         | 519                 |
| Underground Parking            | 349                 |
| Surface Level Parking          | 122                 |
| Total Parking Provided         | 471                 |

| GENERAL SITE STATISTICS              |                     |
|--------------------------------------|---------------------|
| Gross Construction Area Total (m²)   | 26,075              |
| Parking Level GCA (m²)               | 10,157              |
| Residential Unit GCA (m²)            | 12,716              |
| Residential Amenity/Service GCA (m²) | 3,202               |
| Retail GCA (m²)                      | -                   |
| Exclusions                           | 10,710              |
| Gross Floor Area (m²)                | 15,365              |
| UNIT STATISTICS                      |                     |
| Total Number of Units                | 159                 |
| Average Unit GFA (m2)                | 80.0                |
| Average Unit GFA (Sq.ft)             | 860.8               |
| PARKING                              |                     |
| Required Resident Parking            | 1.5 Spaces/Unit 239 |
| Required Visitor Parking             | 0.25 Spaces/Unit 40 |
| Total Required Parking               | 278                 |
| Underground Parking                  | 243                 |
| Above grade Parking                  | 45                  |
| Total Parking Provided               | 288                 |

---

## **Appendix B: Background Information**

---

RECEIVED

NOV 09 2006



## DUFFERIN-PEEL CATHOLIC DISTRICT SCHOOL BOARD

40 Matheson Boulevard West, Mississauga Ontario L5R 1C5 • Tel: (905) 890-1221 • Fax: (905) 890-1557

**DATE:** November 8, 2006

**TO:** Alan Young, Weston Consulting Group Inc.

**FROM:** Beth Bjarnason, Manager of Planning

**RE:** Servicing Investigation for Columbia Way

---

Please find attached a copy of the Servicing Investigation undertaken for the Board related to St. Michael Secondary School.



July 13, 2006  
File: 10-06629

Mr Ken MacSporran  
Moffet and Duncan Architects Inc  
5052 Dundas Street West  
Islington, Ontario M9A 1B9

Dear Mr. MacSporran

**Subject: Servicing Investigation  
Bolton Secondary School  
Town of Caledon**

As requested we have undertaken a Servicing Investigation for a potential school site in the Town of Caledon. The Dufferin-Peel Catholic District School Board is considering a new secondary school site in Bolton. The school site is located on the north side of Columbia Way, east of Kingsview Drive (which is the first street east of Highway 50). Currently, there is no development on the north side of Columbia Way. The proposed school site is 6.1 ha in size (roughly 200m x 300m). The attached figure shows the location of the proposed school block and other potential development north of Columbia Way.

This investigation has been conducted for the sole purpose of determining the location and capacity of existing municipal services and utilities adjacent to the site. This investigation does not consider any of the planning issues related to this site as this is beyond the scope of work.

The following services/utilities have been reviewed in this investigation:

- Watermain
- Sanitary Sewers
- Storm sewers
- Gas
- Hydro
- Bell
- Cable TV
- Sidewalks

We have discussed each of these services with the various utilities and approval agencies and have been advised of the following:

#### **Watermain**

The Region of Peel has provided a copy of an engineering drawing (Project No. 350E-86, Drawing No. 24311-D) which was prepared for the subdivision located on the south side of



Columbia Way. A copy of this drawing is attached for information purposes. This drawing shows that a 400mm concrete watermain, located on the east side of Kingsview Drive, has been constructed across Columbia Way to the north side. This watermain is plugged 1.5m north of the north streetline and is intended to be extended when development proceeds north of Columbia Way. A 400mm diameter watermain is of sufficient size to service the lands north of Columbia Way, including the school site

### **Sanitary Sewer**

As part of the development of the subdivision located south of Columbia Way, the sanitary sewer was extended across Columbia Way to the north boulevard. A sanitary manhole has been constructed 1.5m north of the north streetline. The sanitary sewer is a 250mm diameter pipe constructed at 0.57%. This sewer has a capacity of 46.8 l/s.

For a high school site of 6.1ha, the expected peak flow would be approximately 8 l/s. Including the 5.3 ha commercial area and the 3.1 ha residential area, the total expected peak flow for the lands north of Columbia Way would be approximately 29 l/s. To be conservative we have assumed the residential block would be developed as medium density. If it is developed as low density the total expected peak flow from the lands north of Columbia Way would be reduced to about 21.5 l/s. Therefore it would appear that this sewer has the necessary capacity to accommodate the school site. We have requested additional information from the Region on the existing system located south of Columbia Way in order to confirm that available capacity exists in the downstream sewers. The Region has indicated that they will be able to provide this information to us in one to two weeks.



### **Storm Sewer**

Similar to sanitary, when the development south of Columbia Way was designed, it included the extension of a storm sewer across Columbia Way to the north side of the road. A storm manhole has been constructed 1.5m north of the north streetline of Columbia Way. The storm sewer is a 1050mm diameter sewer constructed at 0.36% (designed at 0.50%). This sewer has a capacity of 1,709 l/s. The Town of Caledon has indicated that the Stormwater Management Report includes an external drainage area north of Columbia Way of 9.70 ha. However the boundaries of this area were not identified.

The Town has advised that they will require on-site SWM controls consisting of:

- Roof top controls with a maximum release rate of 42 l/s/ha.
- 100 year maximum release rate for site is 180 l/s/ha.


To achieve these maximum release rates it will be necessary to design the parking lot grading to provide surface storage. The required amount of storage will be determined at detailed design.



GENERAL NOTES:  
SEE Dwg. No. 6

| NO. | REVISION                | DATE     | BY          | CHKD. | APP'D. |
|-----|-------------------------|----------|-------------|-------|--------|
| 1   | ISSUED FOR PERMIT       | 10/10/00 | ANTON KILAS |       |        |
| 2   | REVISED TO SHOW CHANGES | 10/10/00 | ANTON KILAS |       |        |
| 3   | REVISED TO SHOW CHANGES | 10/10/00 | ANTON KILAS |       |        |
| 4   | REVISED TO SHOW CHANGES | 10/10/00 | ANTON KILAS |       |        |
| 5   | REVISED TO SHOW CHANGES | 10/10/00 | ANTON KILAS |       |        |

**BENCH MARK:** H.C.C. BM 100009-ELEV. 262.7240 ± 20.000  
STATION 0+000.00. THIS MARK IS LOCATED ON THE WEST SIDE OF KINGSVIEW DRIVE, 100' NORTH OF THE INTERSECTION OF KINGSVIEW DRIVE AND COLUMBIA WAY. THE MARK IS A 10" DIA. IRON PIPE SET IN CONCRETE. THE MARK IS 10' NORTH OF THE INTERSECTION OF KINGSVIEW DRIVE AND COLUMBIA WAY. THE MARK IS 10' NORTH OF THE INTERSECTION OF KINGSVIEW DRIVE AND COLUMBIA WAY.



**WYNDCLIFFE SUBDIVISION**  
PROJECT NAME: T-86001

**Anton Kilas Limited**  
CONSULTANT

**TOWN OF CALEDON**

**KINGSVIEW DRIVE**  
STN 0+000 TO STN 0+260

SCALE: 1" = 40' (PLAN) 1" = 10' (SECTION)  
APPROVED BY: [Signature]  
DATE: 10/10/00  
CHECKED BY: [Signature]  
DATE: 10/10/00



### **Gas**

We spoke with Mr. Jim Arnott and Ms. Beverly Poersch of Enbridge. There is an existing 4" (100mm) gas main located in the north boulevard of Columbia Way. They have indicated that they have no concerns with providing service to the school site.

### **Hydro**

We spoke with Mr. Bob Harper of Hydro One. There is an existing overhead hydro line located on the north side of Columbia Way across the frontage of the proposed school site. The existing line is a 3 phase 27.6 kV line. Hydro One advised that they can provide for a peak load of 1000 KVA from the school. A pole mounted transformer can be provided to reduce the hydro flow to 500 KVA. If greater transformation is required then a pad mount transformer located on the school property will be required.

### **Bell Canada**

We spoke with Mr. Ron Blair of Bell Canada. Currently they do not have any service within the north boulevard of Columbia Way. All of their facility is located within the subdivision on the south side. They also have an existing line on the east side of Highway 50. They indicated that they could provide service to the school by either installing a road crossing at Kingsview Drive or by installing a new line on the hydro poles along the north side of Columbia Way from Highway 50. Therefore, Bell service can be made to this site.

### **Cable TV**

We spoke with Mr. Carston Schunelle of Rogers. There is an existing fibre optic node located at the southwest corner of Kingsview Avenue and Columbia Way. In addition, a conduit has been pre-installed across Columbia Way to the north side. This will facilitate the northward extension of a fibre optic line to the lands north of Columbia Way. Therefore, there are no issues with servicing the school site with Cable TV.

### **Sidewalks**

There are currently no sidewalks constructed on Columbia Way. There is a sidewalk constructed on the west side of Kingsview Avenue which extends to Columbia Way. This provides pedestrian access to Columbia Way for the existing subdivision located to the south. In the future, there will be sidewalks constructed on both sides of Columbia Way. The Town currently has no plans for constructing any sidewalks on Columbia Way. This will occur in due course as development advances in this area.

The location of the above services are illustrated on Figure No.1.



## Site Topography

Based on the draft copy of the topographic survey prepared by Young & Young Surveying Inc. the west half of the site is relatively flat and the east half of the site slopes off toward the environmentally protected lands and ultimately to an eastern tributary of the Humber River.

The as-built storm and sanitary sewer inverts are both noted as 259.33m on the attached engineering drawing. There appears to be a 0.611m adjustment noted in the benchmark description on that drawing. In comparing the centerline road elevation at Columbia Way and Kingsview Drive there also appears to be a difference of about 0.60m to 0.70m between the topo survey and the engineering drawing. The draft topo survey shows a lower elevation at this intersection which means the as-built inverts relative to the current topo survey may be closer to 258.70m.

It is assumed that the school building will be located on the western portion of the site adjacent to Kingsview Drive. The average ground elevation on the western half of the site is about 264.50m. Assuming the first floor elevation will also be around 264.50m, there will not be any issue with providing sanitary and storm connections to this building (i.e. FFE will be more than 5.0m higher than existing invert elevations).

It is expected that the east half of the site will be developed as the track and field. Storm drainage from this area will need to sheet drain to the east as the elevations are too low to be picked up by the storm sewer. It is not expected that any quantity or quality controls will be required for this area as it will be predominantly a grassed area.

## Summary

All of the necessary services for the proposed school in Bolton are located at the intersection of Kingsview Drive and Columbia Way and/or within the north boulevard of Columbia Way across the frontage of the school block.

Since all of the services are located in close proximity to the site it will not be necessary to extend services very far. We have queried the Municipality on whether or not they will require the services to be extended north along the future extension of Kingsview Drive (north of Columbia Way) to the centre of the school block. They have indicated that it is too premature to say whether this will be required or not. They will not respond until they see a site plan submission.

Therefore, in terms of external servicing costs we would suggest an allowance be carried to extend the storm, sanitary and water services a short distance north (say 20m) and then into the site. We suggest the following allowances be carried for external municipal servicing:

- Storm - \$50,000
- Sanitary - \$25,000
- Water - \$10,000

Mr Ken MacSporran  
Servicing Investigation  
10-06629  
July 13, 2006  
Page 5



A temporary easement across the land owners property will be required for these services.

We trust this servicing investigation provides the information needed at this time. Please call if you have any questions

Yours very truly

**MARSHALL MACKLIN MONAGHAN LIMITED**

Craig A. Rose, C.E.T.  
Design Manager  
Durham Region Office

CAR:sg  
Encl



---

## **Appendix C: Stormwater Management Calculations**

---



**urbanworks**  
ENGINEERING CORPORATION

Prepared By: M.P.

**Rational Method  
Pre-Development Flow Calculation**

Columbia Square  
File No.: 21-0012CA  
Date: December 2021

**Time of Concentration Calculation (Bransby Williams)**

| Area Number | Area<br>(ha) | C    | Flow Length<br>(m) | $\Delta H$<br>(m) | Slope<br>(%) | Time of<br>Concentration<br>(minutes) |
|-------------|--------------|------|--------------------|-------------------|--------------|---------------------------------------|
| Pre-A1      | 3.30         | 0.25 | 284                | 9.6               | 3.4%         | <b>28.3</b>                           |

**Rational Method Calculation**

Event 2 yr  
IDF Data Set Town of Caledon  
A = 1070.00  
B = 7.850  
C = 0.8759

| Area Number | A<br>(ha) | C    | AC   | Tc<br>(min) | I<br>(mm/h) | Q<br>(m <sup>3</sup> /s) | Q<br>(L/s) |
|-------------|-----------|------|------|-------------|-------------|--------------------------|------------|
| Pre-A1      | 3.30      | 0.25 | 0.83 | 28          | 46.2        | 0.106                    | 105.9      |

Event 5yr  
IDF Data Set Town of Caledon  
A = 1593.00  
B = 11.000  
C = 0.8789

| Area Number | A<br>(ha) | C    | AC   | Tc<br>(min) | I<br>(mm/h) | Q<br>(m <sup>3</sup> /s) | Q<br>(L/s) |
|-------------|-----------|------|------|-------------|-------------|--------------------------|------------|
| Pre-A1      | 3.30      | 0.25 | 0.83 | 28          | 63.2        | 0.145                    | 144.9      |

Event 10yr  
IDF Data Set City of Brampton  
A = 2221.00  
B = 12.000  
C = 0.9080

| Area Number | A<br>(ha) | C    | AC   | Tc<br>(min) | I<br>(mm/h) | Q<br>(m <sup>3</sup> /s) | Q<br>(L/s) |
|-------------|-----------|------|------|-------------|-------------|--------------------------|------------|
| Pre-A1      | 3.30      | 0.25 | 0.83 | 28          | 77.5        | 0.178                    | 177.5      |



Prepared By: M.P.

## Rational Method Pre-Development Flow Calculation

Columbia Square  
File No.: 21-0012CA  
Date: December 2021

### Time of Concentration Calculation

| Area Number | Area<br>(ha) | C    | Flow Length<br>(m) | $\Delta H$<br>(m) | Slope<br>(%) | Time of<br>Concentration<br>(minutes) |
|-------------|--------------|------|--------------------|-------------------|--------------|---------------------------------------|
| Pre-A1      | 3.30         | 0.25 | 284                | 9.6               | 3.4%         | 28.3                                  |

### Rational Method Calculation

Event 25 yr  
IDF Data Set Town of Caledon  
A = 3158.00  
B = 15.000  
C = 0.9335

| Area Number | A<br>(ha) | C    | AC   | Tc<br>(min) | I<br>(mm/h) | Q<br>(m3/s) | Q<br>(L/s) |
|-------------|-----------|------|------|-------------|-------------|-------------|------------|
| Pre-A1      | 3.30      | 0.25 | 0.83 | 28          | 93.7        | 0.215       | 214.8      |

Event 50yr  
IDF Data Set Town of Caledon  
A = 3886.00  
B = 16.000  
C = 0.9495

| Area Number | A<br>(ha) | C    | AC   | Tc<br>(min) | I<br>(mm/h) | Q<br>(m3/s) | Q<br>(L/s) |
|-------------|-----------|------|------|-------------|-------------|-------------|------------|
| Pre-A1      | 3.30      | 0.25 | 0.83 | 28          | 106.3       | 0.244       | 243.5      |

Event 100yr  
IDF Data Set City of Brampton  
A = 4688.00  
B = 17.000  
C = 0.9624

| Area Number | A<br>(ha) | C    | AC   | Tc<br>(min) | I<br>(mm/h) | Q<br>(m3/s) | Q<br>(L/s) |
|-------------|-----------|------|------|-------------|-------------|-------------|------------|
| Pre-A1      | 3.30      | 0.25 | 0.83 | 28          | 119.5       | 0.274       | 273.8      |



Prepared by: M.P.

## ALLOWABLE RELEASE RATE CALCULATION

### ENTIRE SITE

Columbia Square, Caledon

File No.: 21-0012CA

Date: Jan 2022

#### Gross Allowable Release Rate

Allowable Release Rate = 180 L/s/ha  
 Area = 3.30 ha  
 Q = 594.0 L/s


#### Uncontrolled Flow


Area ID = 4  
 Area (ha) = 0.22  
 C = 0.90  
 Tc (minutes) = 10


| Return Period | a    | b    | c      | Intensity<br>(mm/hr) | Flow<br>(L/s) |
|---------------|------|------|--------|----------------------|---------------|
| 2-yr          | 1070 | 7.85 | 0.8759 | 85.7                 | 47.1          |
| 5-yr          | 1593 | 11   | 0.8789 | 109.7                | 60.3          |
| 10-yr         | 2221 | 12   | 0.908  | 134.2                | 73.8          |
| 25-yr         | 3158 | 15   | 0.9335 | 156.5                | 86.1          |
| 50-yr         | 3886 | 16   | 0.9495 | 176.2                | 96.9          |
| 100-yr        | 4688 | 17   | 0.9624 | 196.5                | 108.1         |


#### Net Allowable Release Rate

| Return Period | Allowable<br>Release Rate<br>(L/s) | Uncontrolled<br>Flow<br>(L/s) | Net Allowable<br>Release Rate<br>(L/s) | Revised Unit<br>Flow Rate<br>(L/s/ha) |
|---------------|------------------------------------|-------------------------------|--|---------------------------------------|
| 100-yr        | 594.0                              | 108.1                         | 485.9                                  | 158                                   |

|  |                               |   |                                    |                                      |   |
|--|-------------------------------|---|------------------------------------|--------------------------------------|---|
| <br>Prepared by: M.P. |                               | <b>Modified Rational Method - 100 Year Storage</b>  |                                    |                                      |   |
|  |                               | <b>AREA 1A</b><br>Columbia Square<br>File No.: 21-0012CA<br>Date: Jan 2022  |                                    |                                      |   |
|  |                               | Drainage Areas A1 Post<br>Area = 0.50 ha<br>"C" = 0.90<br>AC1= 0.45<br>Tc = 10.0 min<br>Time Increment = 5.0 min<br>Release Rate = 78.9 l/s<br>Max.Storage Required = 123.0 m <sup>3</sup><br>Max Ponding Depth = 0.00 m<br>Head Elevation = 0.00 m |                                    |                                      |   |
| 100 Year   |                               |   |                                    |                                      |   |
| a=   | 4688.00                       |   |                                    |                                      |   |
| b=   | 17.000                        |   |                                    |                                      |   |
| c=   | 0.9624                        |   |                                    |                                      |   |
| (1)  | (2)                           | (3)   | (4)                                | (5)                                  | (6)   |
| Time<br>(min)  | Rainfall Intensity<br>(mm/hr) | Storm Runoff<br>(m <sup>3</sup> /s)   | Runoff Volume<br>(m <sup>3</sup> ) | Released Volume<br>(m <sup>3</sup> ) | Required Storage<br>Volume<br>(m <sup>3</sup> ) |
|  |                               | (3) = [(2)*AC1]/360   | (4) = (3)*(1)*60                   | (5) = [(R2) / 1000]*(1)*60           | (6) = (4)-(5)                                   |
| 10.0   | 196.5                         | 0.246   | 147.40                             | 47.33                                | 100.07  |
| 15.0   | 166.9                         | 0.209   | 187.75                             | 70.99                                | 116.76  |
| 20.0   | 145.1                         | 0.181   | 217.69                             | 94.66                                | 123.03  |
| 25.0   | 128.5                         | 0.161   | 240.87                             | 118.32                               | 122.54  |
| 30.0   | 115.3                         | 0.144   | 259.38                             | 141.99                               | 117.40  |
| 35.0   | 104.6                         | 0.131   | 274.56                             | 165.65                               | 108.91  |
| 40.0   | 95.7                          | 0.120   | 287.25                             | 189.31                               | 97.93   |
| 45.0   | 88.3                          | 0.110   | 298.03                             | 212.98                               | 85.05   |
| 50.0   | 82.0                          | 0.102   | 307.33                             | 236.64                               | 70.69   |
| 55.0   | 76.5                          | 0.096   | 315.44                             | 260.31                               | 55.13   |
| 60.0   | 71.7                          | 0.090   | 322.58                             | 283.97                               | 38.61   |
| 65.0   | 67.5                          | 0.084   | 328.93                             | 307.63                               | 21.30   |
| 70.0   | 63.7                          | 0.080   | 334.62                             | 331.30                               | 3.32  |
| 75.0   | 60.4                          | 0.076   | 339.75                             | 354.96                               | 0.00  |
| 80.0   | 57.4                          | 0.072   | 344.41                             | 378.63                               | 0.00  |
| 85.0   | 54.7                          | 0.068   | 348.65                             | 402.29                               | 0.00  |
| 90.0   | 52.2                          | 0.065   | 352.54                             | 425.96                               | 0.00  |
| 95.0   | 50.0                          | 0.062   | 356.13                             | 449.62                               | 0.00  |
| 100.0  | 47.9                          | 0.060   | 359.44                             | 473.28                               | 0.00  |
| 105.0  | 46.0                          | 0.058   | 362.51                             | 496.95                               | 0.00  |
| 110.0  | 44.3                          | 0.055   | 365.38                             | 520.61                               | 0.00  |
| 115.0  | 42.7                          | 0.053   | 368.05                             | 544.28                               | 0.00  |
| 120.0  | 41.2                          | 0.051   | 370.55                             | 567.94                               | 0.00  |
| 125.0  | 39.8                          | 0.050   | 372.90                             | 591.61                               | 0.00  |
| 130.0  | 38.5                          | 0.048   | 375.12                             | 615.27                               | 0.00  |
| 135.0  | 37.3                          | 0.047   | 377.20                             | 638.93                               | 0.00  |
| 140.0  | 36.1                          | 0.045   | 379.18                             | 662.60                               | 0.00  |
| 145.0  | 35.0                          | 0.044   | 381.05                             | 686.26                               | 0.00  |
| 150.0  | 34.0                          | 0.043   | 382.82                             | 709.93                               | 0.00  |
| 155.0  | 33.1                          | 0.041   | 384.51                             | 733.59                               | 0.00  |
| 160.0  | 32.2                          | 0.040   | 386.12                             | 757.25                               | 0.00  |
| 165.0  | 31.3                          | 0.039   | 387.65                             | 780.92                               | 0.00  |

|  |                               |   |                                    |                                      |   |
|--|-------------------------------|---|------------------------------------|--------------------------------------|---|
| <br>Prepared by: M.P. |                               | <b>Modified Rational Method - 100 Year Storage</b><br><b>AREA 1B</b><br>Columbia Square<br>File No.: 21-0012CA<br>Date: Jan 2022  |                                    |                                      |   |
|  |                               | Drainage Areas A1 Post<br>Area = <b>0.68</b> ha<br>"C" = <b>0.90</b><br>AC1= <b>0.61</b><br>Tc = <b>10.0</b> min<br>Time Increment = <b>5.0</b> min<br>Release Rate = <b>107.3</b> l/s<br>Max.Storage Required = <b>167.3</b> m <sup>3</sup><br>Max Ponding Depth = <b>0.00</b> m<br>Head Elevation = <b>0.00</b> m |                                    |                                      |   |
| 100 Year   |                               |   |                                    |                                      |   |
| a=   | 4688.00                       |   |                                    |                                      |   |
| b=   | 17.000                        |   |                                    |                                      |   |
| c=   | 0.9624                        |   |                                    |                                      |   |
| (1)  | (2)                           | (3)   | (4)                                | (5)                                  | (6)   |
| Time<br>(min)  | Rainfall Intensity<br>(mm/hr) | Storm Runoff<br>(m <sup>3</sup> /s)   | Runoff Volume<br>(m <sup>3</sup> ) | Released Volume<br>(m <sup>3</sup> ) | Required Storage<br>Volume<br>(m <sup>3</sup> ) |
|  |                               | (3) = [(2)*AC1]/360   | (4) = (3)*(1)*60                   | (5) = [(R2) / 1000]*(1)*60           | (6) = (4)-(5)                                   |
| 10.0   | 196.5                         | 0.334   | 200.47                             | 64.37                                | 136.10  |
| 15.0   | 166.9                         | 0.284   | 255.34                             | 96.55                                | 158.79  |
| 20.0   | 145.1                         | 0.247   | 296.06                             | 128.73                               | 167.33  |
| 25.0   | 128.5                         | 0.218   | 327.58                             | 160.92                               | 166.66  |
| 30.0   | 115.3                         | 0.196   | 352.76                             | 193.10                               | 159.66  |
| 35.0   | 104.6                         | 0.178   | 373.40                             | 225.28                               | 148.12  |
| 40.0   | 95.7                          | 0.163   | 390.66                             | 257.47                               | 133.19  |
| 45.0   | 88.3                          | 0.150   | 405.32                             | 289.65                               | 115.67  |
| 50.0   | 82.0                          | 0.139   | 417.97                             | 321.83                               | 96.14   |
| 55.0   | 76.5                          | 0.130   | 429.00                             | 354.02                               | 74.98   |
| 60.0   | 71.7                          | 0.122   | 438.71                             | 386.20                               | 52.51   |
| 65.0   | 67.5                          | 0.115   | 447.35                             | 418.38                               | 28.97   |
| 70.0   | 63.7                          | 0.108   | 455.08                             | 450.57                               | 4.52  |
| 75.0   | 60.4                          | 0.103   | 462.06                             | 482.75                               | 0.00  |
| 80.0   | 57.4                          | 0.098   | 468.39                             | 514.93                               | 0.00  |
| 85.0   | 54.7                          | 0.093   | 474.17                             | 547.12                               | 0.00  |
| 90.0   | 52.2                          | 0.089   | 479.46                             | 579.30                               | 0.00  |
| 95.0   | 50.0                          | 0.085   | 484.33                             | 611.48                               | 0.00  |
| 100.0  | 47.9                          | 0.081   | 488.84                             | 643.67                               | 0.00  |
| 105.0  | 46.0                          | 0.078   | 493.02                             | 675.85                               | 0.00  |
| 110.0  | 44.3                          | 0.075   | 496.91                             | 708.03                               | 0.00  |
| 115.0  | 42.7                          | 0.073   | 500.55                             | 740.22                               | 0.00  |
| 120.0  | 41.2                          | 0.070   | 503.95                             | 772.40                               | 0.00  |
| 125.0  | 39.8                          | 0.068   | 507.15                             | 804.58                               | 0.00  |
| 130.0  | 38.5                          | 0.065   | 510.16                             | 836.77                               | 0.00  |
| 135.0  | 37.3                          | 0.063   | 513.00                             | 868.95                               | 0.00  |
| 140.0  | 36.1                          | 0.061   | 515.68                             | 901.13                               | 0.00  |
| 145.0  | 35.0                          | 0.060   | 518.23                             | 933.32                               | 0.00  |
| 150.0  | 34.0                          | 0.058   | 520.64                             | 965.50                               | 0.00  |
| 155.0  | 33.1                          | 0.056   | 522.93                             | 997.68                               | 0.00  |
| 160.0  | 32.2                          | 0.055   | 525.12                             | 1029.87                              | 0.00  |
| 165.0  | 31.3                          | 0.053   | 527.20                             | 1062.05                              | 0.00  |

|  |                               |  |                                    |                                      |   |
|--|-------------------------------|--|------------------------------------|--------------------------------------|---|
| <br>Prepared by: M.P. |                               | Modified Rational Method - 100 Year Storage  |                                    |                                      |   |
|  |                               | <b>AREA 2</b><br>Columbia Square<br>File No.: 21-0012CA<br>Date: Jan 2022  |                                    |                                      |   |
|  |                               | Drainage Areas A1 Post<br>Area = 1.29 ha<br>"C" = 0.90<br>AC1= 1.16<br>Tc = 10.0 min<br>Time Increment = 5.0 min<br>Release Rate = 203.5 l/s<br>Max.Storage Required = 317.4 m <sup>3</sup><br>Max Ponding Depth = 0.00 m<br>Head Elevation = 0.00 m |                                    |                                      |   |
| 100 Year   |                               |  |                                    |                                      |   |
| a=   | 4688.00                       |  |                                    |                                      |   |
| b=   | 17.000                        |  |                                    |                                      |   |
| c=   | 0.9624                        |  |                                    |                                      |   |
| (1)  | (2)                           | (3)  | (4)                                | (5)                                  | (6)   |
| Time<br>(min)  | Rainfall Intensity<br>(mm/hr) | Storm Runoff<br>(m <sup>3</sup> /s)  | Runoff Volume<br>(m <sup>3</sup> ) | Released Volume<br>(m <sup>3</sup> ) | Required Storage<br>Volume<br>(m <sup>3</sup> ) |
|  |                               | (3) = [(2)*AC1]/360  | (4) = (3)*(1)*60                   | (5) = [(R2) / 1000]*(1)*60           | (6) = (4)-(5)                                   |
| 10.0   | 196.5                         | 0.634  | 380.30                             | 122.11                               | 258.19  |
| 15.0   | 166.9                         | 0.538  | 484.40                             | 183.16                               | 301.24  |
| 20.0   | 145.1                         | 0.468  | 561.64                             | 244.21                               | 317.43  |
| 25.0   | 128.5                         | 0.414  | 621.43                             | 305.27                               | 316.16  |
| 30.0   | 115.3                         | 0.372  | 669.21                             | 366.32                               | 302.89  |
| 35.0   | 104.6                         | 0.337  | 708.36                             | 427.38                               | 280.99  |
| 40.0   | 95.7                          | 0.309  | 741.10                             | 488.43                               | 252.67  |
| 45.0   | 88.3                          | 0.285  | 768.92                             | 549.48                               | 219.44  |
| 50.0   | 82.0                          | 0.264  | 792.91                             | 610.54                               | 182.37  |
| 55.0   | 76.5                          | 0.247  | 813.83                             | 671.59                               | 142.24  |
| 60.0   | 71.7                          | 0.231  | 832.26                             | 732.64                               | 99.62   |
| 65.0   | 67.5                          | 0.218  | 848.65                             | 793.70                               | 54.95   |
| 70.0   | 63.7                          | 0.206  | 863.32                             | 854.75                               | 8.57  |
| 75.0   | 60.4                          | 0.195  | 876.56                             | 915.80                               | 0.00  |
| 80.0   | 57.4                          | 0.185  | 888.57                             | 976.86                               | 0.00  |
| 85.0   | 54.7                          | 0.176  | 899.52                             | 1037.91                              | 0.00  |
| 90.0   | 52.2                          | 0.168  | 909.56                             | 1098.97                              | 0.00  |
| 95.0   | 50.0                          | 0.161  | 918.81                             | 1160.02                              | 0.00  |
| 100.0  | 47.9                          | 0.155  | 927.36                             | 1221.07                              | 0.00  |
| 105.0  | 46.0                          | 0.148  | 935.29                             | 1282.13                              | 0.00  |
| 110.0  | 44.3                          | 0.143  | 942.67                             | 1343.18                              | 0.00  |
| 115.0  | 42.7                          | 0.138  | 949.57                             | 1404.23                              | 0.00  |
| 120.0  | 41.2                          | 0.133  | 956.03                             | 1465.29                              | 0.00  |
| 125.0  | 39.8                          | 0.128  | 962.09                             | 1526.34                              | 0.00  |
| 130.0  | 38.5                          | 0.124  | 967.80                             | 1587.39                              | 0.00  |
| 135.0  | 37.3                          | 0.120  | 973.19                             | 1648.45                              | 0.00  |
| 140.0  | 36.1                          | 0.116  | 978.28                             | 1709.50                              | 0.00  |
| 145.0  | 35.0                          | 0.113  | 983.10                             | 1770.56                              | 0.00  |
| 150.0  | 34.0                          | 0.110  | 987.68                             | 1831.61                              | 0.00  |
| 155.0  | 33.1                          | 0.107  | 992.04                             | 1892.66                              | 0.00  |
| 160.0  | 32.2                          | 0.104  | 996.18                             | 1953.72                              | 0.00  |
| 165.0  | 31.3                          | 0.101  | 1000.14                            | 2014.77                              | 0.00  |

|  |                               |   |                                    |                                      |   |
|--|-------------------------------|---|------------------------------------|--------------------------------------|---|
| <br>Prepared by: M.P. |                               | <b>Modified Rational Method - 100 Year Storage</b>  |                                    |                                      |   |
|  |                               | <b>AREA 3</b><br>Columbia Square<br>File No.: 21-0012CA<br>Date: Jan 2022   |                                    |                                      |   |
|  |                               | Drainage Areas A1 Post<br>Area = 0.61 ha<br>"C" = 0.90<br>AC1= 0.55<br>Tc = 10.0 min<br>Time Increment = 5.0 min<br>Release Rate = 96.2 l/s<br>Max.Storage Required = 150.1 m <sup>3</sup><br>Max Ponding Depth = 0.00 m<br>Head Elevation = 0.00 m |                                    |                                      |   |
| 100 Year   |                               |   |                                    |                                      |   |
| a=   | 4688.00                       |   |                                    |                                      |   |
| b=   | 17.000                        |   |                                    |                                      |   |
| c=   | 0.9624                        |   |                                    |                                      |   |
| (1)  | (2)                           | (3)   | (4)                                | (5)                                  | (6)   |
| Time<br>(min)  | Rainfall Intensity<br>(mm/hr) | Storm Runoff<br>(m <sup>3</sup> /s)   | Runoff Volume<br>(m <sup>3</sup> ) | Released Volume<br>(m <sup>3</sup> ) | Required Storage<br>Volume<br>(m <sup>3</sup> ) |
|  |                               | (3) = [(2)*AC1]/360   | (4) = (3)*(1)*60                   | (5) = [(R2) / 1000]*(1)*60           | (6) = (4)-(5)                                   |
| 10.0   | 196.5                         | 0.300   | 179.83                             | 57.74                                | 122.09  |
| 15.0   | 166.9                         | 0.255   | 229.06                             | 86.61                                | 142.45  |
| 20.0   | 145.1                         | 0.221   | 265.58                             | 115.48                               | 150.10  |
| 25.0   | 128.5                         | 0.196   | 293.86                             | 144.35                               | 149.50  |
| 30.0   | 115.3                         | 0.176   | 316.45                             | 173.22                               | 143.23  |
| 35.0   | 104.6                         | 0.160   | 334.96                             | 202.09                               | 132.87  |
| 40.0   | 95.7                          | 0.146   | 350.44                             | 230.96                               | 119.48  |
| 45.0   | 88.3                          | 0.135   | 363.60                             | 259.83                               | 103.77  |
| 50.0   | 82.0                          | 0.125   | 374.94                             | 288.70                               | 86.24   |
| 55.0   | 76.5                          | 0.117   | 384.84                             | 317.57                               | 67.26   |
| 60.0   | 71.7                          | 0.109   | 393.55                             | 346.44                               | 47.11   |
| 65.0   | 67.5                          | 0.103   | 401.30                             | 375.31                               | 25.98   |
| 70.0   | 63.7                          | 0.097   | 408.24                             | 404.18                               | 4.05  |
| 75.0   | 60.4                          | 0.092   | 414.50                             | 433.05                               | 0.00  |
| 80.0   | 57.4                          | 0.088   | 420.17                             | 461.93                               | 0.00  |
| 85.0   | 54.7                          | 0.083   | 425.35                             | 490.80                               | 0.00  |
| 90.0   | 52.2                          | 0.080   | 430.10                             | 519.67                               | 0.00  |
| 95.0   | 50.0                          | 0.076   | 434.48                             | 548.54                               | 0.00  |
| 100.0  | 47.9                          | 0.073   | 438.52                             | 577.41                               | 0.00  |
| 105.0  | 46.0                          | 0.070   | 442.27                             | 606.28                               | 0.00  |
| 110.0  | 44.3                          | 0.068   | 445.76                             | 635.15                               | 0.00  |
| 115.0  | 42.7                          | 0.065   | 449.02                             | 664.02                               | 0.00  |
| 120.0  | 41.2                          | 0.063   | 452.07                             | 692.89                               | 0.00  |
| 125.0  | 39.8                          | 0.061   | 454.94                             | 721.76                               | 0.00  |
| 130.0  | 38.5                          | 0.059   | 457.64                             | 750.63                               | 0.00  |
| 135.0  | 37.3                          | 0.057   | 460.19                             | 779.50                               | 0.00  |
| 140.0  | 36.1                          | 0.055   | 462.60                             | 808.37                               | 0.00  |
| 145.0  | 35.0                          | 0.053   | 464.88                             | 837.24                               | 0.00  |
| 150.0  | 34.0                          | 0.052   | 467.04                             | 866.11                               | 0.00  |
| 155.0  | 33.1                          | 0.050   | 469.10                             | 894.98                               | 0.00  |
| 160.0  | 32.2                          | 0.049   | 471.06                             | 923.85                               | 0.00  |
| 165.0  | 31.3                          | 0.048   | 472.93                             | 952.72                               | 0.00  |



## Stormceptor®EF Sizing Report

## STORMCEPTOR®

## ESTIMATED NET ANNUAL SEDIMENT (TSS) LOAD REDUCTION

01/10/2022

|                              |                 |                   |                                    |
|------------------------------|-----------------|-------------------|------------------------------------|
| Province:                    | Ontario         | Project Name:     | Columbia Square                    |
| City:                        | Caledon         | Project Number:   | 21-0012CA                          |
| Nearest Rainfall Station:    | TORONTO INTL AP | Designer Name:    | Michael Paulo                      |
| Climate Station Id:          | 6158731         | Designer Company: | Urbanworks Engineering Corporation |
| Years of Rainfall Data:      | 20              | Designer Email:   | mpaulo@urbanworkseng.com           |
| Site Name:                   |                 | Designer Phone:   | 416-503-4500                       |
| Drainage Area (ha):          | 3.3             | EOR Name:         |                                    |
| % Imperviousness:            | 100.00          | EOR Company:      |                                    |
| Runoff Coefficient 'c': 0.90 |                 | EOR Email:        |                                    |
| Particle Size Distribution:  | Fine            | EOR Phone:        |                                    |
| Target TSS Removal (%):      | 80.0            |                   |                                    |

|  |        |
|--|--------|
| Required Water Quality Runoff Volume Capture (%):        | 90.00  |
| Estimated Water Quality Flow Rate (L/s):                 | 96.61  |
| Oil / Fuel Spill Risk Site?                              | Yes    |
| Upstream Flow Control?                                   | Yes    |
| Upstream Orifice Control Flow Rate to Stormceptor (L/s): | 594.00 |
| Peak Conveyance (maximum) Flow Rate (L/s):               | 594.00 |
| Site Sediment Transport Rate (kg/ha/yr):                 |        |

**Net Annual Sediment  
(TSS) Load Reduction  
Sizing Summary**

| Stormceptor Model | TSS Removal Provided (%) |
|-------------------|--------------------------|
| EFO4              | 44                       |
| EFO6              | 59                       |
| EFO8              | 70                       |
| EFO10             | 77                       |
| <b>EFO12</b>      | <b>84</b>                |

**Recommended Stormceptor EFO Model:** **EFO12**  
**Estimated Net Annual Sediment (TSS) Load Reduction (%):** **84**  
**Water Quality Runoff Volume Capture (%):** **> 90**

## Stormceptor® EF Sizing Report

### THIRD-PARTY TESTING AND VERIFICATION

► **Stormceptor® EF and Stormceptor® EFO** are the latest evolutions in the Stormceptor® oil-grit separator (OGS) technology series, and are designed to remove a wide variety of pollutants from stormwater and snowmelt runoff. These technologies have been third-party tested in accordance with the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators** and performance has been third-party verified in accordance with the **ISO 14034 Environmental Technology Verification (ETV)** protocol.

### PERFORMANCE

► **Stormceptor® EF and EFO** remove stormwater pollutants through gravity separation and floatation, and feature a patent-pending design that generates positive removal of total suspended solids (TSS) throughout each storm event, including high-intensity storms. Captured pollutants include sediment, free oils, and sediment-bound pollutants such as nutrients, heavy metals, and petroleum hydrocarbons. Stormceptor is sized to remove a high level of TSS from the frequent rainfall events that contribute the vast majority of annual runoff volume and pollutant load. The technology incorporates an internal bypass to convey excessive stormwater flows from high-intensity storms through the device without resuspension and washout (scour) of previously captured pollutants. Proper routine maintenance ensures high pollutant removal performance and protection of downstream waterways.

### PARTICLE SIZE DISTRIBUTION (PSD)

► The **Canadian ETV PSD** shown in the table below was used, or in part, for this sizing. This is the identical PSD that is referenced in the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators** for both sediment removal testing and scour testing. The Canadian ETV PSD contains a wide range of particle sizes in the sand and silt fractions, and is considered reasonably representative of the particle size fractions found in typical urban stormwater runoff.

| Particle Size (µm) | Percent Less Than | Particle Size Fraction (µm) | Percent |
|--------------------|-------------------|-----------------------------|---------|
| 1000               | 100               | 500-1000                    | 5       |
| 500                | 95                | 250-500                     | 5       |
| 250                | 90                | 150-250                     | 15      |
| 150                | 75                | 100-150                     | 15      |
| 100                | 60                | 75-100                      | 10      |
| 75                 | 50                | 50-75                       | 5       |
| 50                 | 45                | 20-50                       | 10      |
| 20                 | 35                | 8-20                        | 15      |
| 8                  | 20                | 5-8                         | 10      |
| 5                  | 10                | 2-5                         | 5       |
| 2                  | 5                 | <2                          | 5       |

## Stormceptor®EF Sizing Report


### Upstream Flow Controlled Results

| Rainfall Intensity (mm / hr)                         | Percent Rainfall Volume (%) | Cumulative Rainfall Volume (%) | Flow Rate (L/s) | Flow Rate (L/min) | Surface Loading Rate (L/min/m²) | Removal Efficiency (%) | Incremental Removal (%) | Cumulative Removal (%) |
|--|-----------------------------|--------------------------------|-----------------|-------------------|---------------------------------|------------------------|-------------------------|------------------------|
| 1  | 22.5                        | 22.5                           | 8.26            | 495.0             | 40.0                            | 100                    | 22.5                    | 22.5                   |
| 2  | 18.4                        | 40.9                           | 16.51           | 991.0             | 79.0                            | 91                     | 16.8                    | 39.3                   |
| 3  | 11.8                        | 52.7                           | 24.77           | 1486.0            | 119.0                           | 88                     | 10.3                    | 49.7                   |
| 4  | 9.2                         | 61.9                           | 33.03           | 1982.0            | 159.0                           | 83                     | 7.7                     | 57.3                   |
| 5  | 7.0                         | 68.9                           | 41.28           | 2477.0            | 198.0                           | 78                     | 5.5                     | 62.8                   |
| 6  | 6.0                         | 74.9                           | 49.54           | 2972.0            | 238.0                           | 76                     | 4.5                     | 67.4                   |
| 7  | 4.3                         | 79.2                           | 57.80           | 3468.0            | 277.0                           | 74                     | 3.2                     | 70.6                   |
| 8  | 3.2                         | 82.4                           | 66.05           | 3963.0            | 317.0                           | 72                     | 2.3                     | 72.8                   |
| 9  | 2.9                         | 85.3                           | 74.31           | 4459.0            | 357.0                           | 71                     | 2.1                     | 74.9                   |
| 10   | 2.4                         | 87.7                           | 82.57           | 4954.0            | 396.0                           | 69                     | 1.6                     | 76.6                   |
| 11   | 1.1                         | 88.7                           | 90.82           | 5449.0            | 436.0                           | 67                     | 0.7                     | 77.3                   |
| 12   | 1.8                         | 90.5                           | 99.08           | 5945.0            | 476.0                           | 66                     | 1.2                     | 78.5                   |
| 13   | 1.5                         | 92.1                           | 107.34          | 6440.0            | 515.0                           | 64                     | 1.0                     | 79.5                   |
| 14   | 1.1                         | 93.1                           | 115.59          | 6936.0            | 555.0                           | 62                     | 0.7                     | 80.1                   |
| 15   | 0.3                         | 93.5                           | 123.85          | 7431.0            | 594.0                           | 60                     | 0.2                     | 80.3                   |
| 16   | 0.9                         | 94.3                           | 132.11          | 7926.0            | 634.0                           | 60                     | 0.5                     | 80.8                   |
| 17   | 0.9                         | 95.3                           | 140.36          | 8422.0            | 674.0                           | 60                     | 0.5                     | 81.4                   |
| 18   | 0.2                         | 95.5                           | 148.62          | 8917.0            | 713.0                           | 59                     | 0.1                     | 81.5                   |
| 19   | 1.6                         | 97.1                           | 156.88          | 9413.0            | 753.0                           | 59                     | 1.0                     | 82.4                   |
| 20   | 0.2                         | 97.3                           | 165.13          | 9908.0            | 793.0                           | 59                     | 0.1                     | 82.6                   |
| 21   | 0.7                         | 98.0                           | 173.39          | 10403.0           | 832.0                           | 58                     | 0.4                     | 83.0                   |
| 22   | 2.0                         | 100.0                          | 181.65          | 10899.0           | 872.0                           | 58                     | 1.2                     | 84.1                   |
| 23   | 0.2                         | 100.2                          | 189.90          | 11394.0           | 912.0                           | 58                     | 0.1                     | 84.3                   |
| 24   | 0.3                         | 100.5                          | 198.16          | 11890.0           | 951.0                           | 58                     | 0.2                     | 84.4                   |
| 25   | 0.3                         | 100.8                          | 206.42          | 12385.0           | 991.0                           | 57                     | 0.2                     | 84.6                   |
| 30   | 1.3                         | 102.0                          | 247.70          | 14862.0           | 1189.0                          | 53                     | 0.7                     | 85.3                   |
| 35   | -2.0                        | 100.0                          | 288.98          | 17339.0           | 1387.0                          | 49                     | N/A                     | 84.3                   |
| 40   | 0.0                         | 100.0                          | 330.26          | 19816.0           | 1585.0                          | 43                     | 0.0                     | 84.3                   |
| 45   | 0.0                         | 100.0                          | 371.55          | 22293.0           | 1783.0                          | 38                     | 0.0                     | 84.3                   |
| 50   | 0.0                         | 100.0                          | 412.83          | 24770.0           | 1982.0                          | 34                     | 0.0                     | 84.3                   |
| Estimated Net Annual Sediment (TSS) Load Reduction = |                             |                                |                 |                   |                                 |                        |                         | 84 %                   |


Climate Station ID: 6158731 Years of Rainfall Data: 20

# Stormceptor®EF Sizing Report

## RAINFALL DATA FROM TORONTO INTL AP RAINFALL STATION



## INCREMENTAL AND CUMULATIVE TSS REMOVAL FOR THE RECOMMENDED STORMCEPTOR® MODEL



## Stormceptor® EF Sizing Report

### Maximum Pipe Diameter / Peak Conveyance

| Stormceptor<br>EF / EFO | Model Diameter |      | Min Angle Inlet /<br>Outlet Pipes | Max Inlet Pipe<br>Diameter |      | Max Outlet Pipe<br>Diameter |      | Peak Conveyance<br>Flow Rate |       |
|-------------------------|----------------|------|-----------------------------------|----------------------------|------|-----------------------------|------|------------------------------|-------|
|                         | (m)            | (ft) |                                   | (mm)                       | (in) | (mm)                        | (in) | (L/s)                        | (cfs) |
| EF4 / EFO4              | 1.2            | 4    | 90                                | 609                        | 24   | 609                         | 24   | 425                          | 15    |
| EF6 / EFO6              | 1.8            | 6    | 90                                | 914                        | 36   | 914                         | 36   | 990                          | 35    |
| EF8 / EFO8              | 2.4            | 8    | 90                                | 1219                       | 48   | 1219                        | 48   | 1700                         | 60    |
| EF10 / EFO10            | 3.0            | 10   | 90                                | 1828                       | 72   | 1828                        | 72   | 2830                         | 100   |
| EF12 / EFO12            | 3.6            | 12   | 90                                | 1828                       | 72   | 1828                        | 72   | 2830                         | 100   |

### SCOUR PREVENTION AND ONLINE CONFIGURATION


► **Stormceptor® EF and EFO** feature an internal bypass and superior scour prevention technology that have been demonstrated in third-party testing according to the scour testing provisions of the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators**, and the exceptional scour test performance has been third-party verified in accordance with the ISO 14034 ETV protocol. As a result, Stormceptor EF and EFO are approved for online installation, eliminating the need for costly additional bypass structures, piping, and installation expense.

### DESIGN FLEXIBILITY


► **Stormceptor® EF and EFO** offers design flexibility in one simplified platform, accepting stormwater flow from a single inlet pipe or multiple inlet pipes, and/or surface runoff through an inlet grate. The device can also serve as a junction structure, accommodate a 90-degree inlet-to-outlet bend angle, and can be modified to ensure performance in submerged conditions.

### OIL CAPTURE AND RETENTION

► While Stormceptor® EF will capture and retain oil from dry weather spills and low intensity runoff, **Stormceptor® EFO** has demonstrated superior oil capture and greater than 99% oil retention in third-party testing according to the light liquid re-entrainment testing provisions of the Canadian ETV **Procedure for Laboratory Testing of Oil-Grit Separators**. Stormceptor EFO is recommended for sites where oil capture and retention is a requirement.



## Stormceptor® EF Sizing Report



### INLET-TO-OUTLET DROP

Elevation differential between inlet and outlet pipe inverts is dictated by the angle at which the inlet pipe(s) enters the unit.

0° - 45° : The inlet pipe is 1-inch (25mm) higher than the outlet pipe.

45° - 90° : The inlet pipe is 2-inches (50mm) higher than the outlet pipe.

### HEAD LOSS

The head loss through Stormceptor EF is similar to that of a 60-degree bend structure. The applicable K value for calculating minor losses through the unit is 1.1.

For submerged conditions the applicable K value is 3.0.

### Pollutant Capacity

| Stormceptor EF / EFO | Model Diameter |      | Depth (Outlet Pipe Invert to Sump Floor) |      | Oil Volume |       | Recommended Sediment Maintenance Depth * |      | Maximum Sediment Volume * |       | Maximum Sediment Mass ** |        |
|----------------------|----------------|------|--|------|------------|-------|--|------|---------------------------|-------|--------------------------|--------|
|                      | (m)            | (ft) | (m)                                      | (ft) | (L)        | (Gal) | (mm)                                     | (in) | (L)                       | (ft³) | (kg)                     | (lb)   |
| EF4 / EFO4           | 1.2            | 4    | 1.52                                     | 5.0  | 265        | 70    | 203                                      | 8    | 1190                      | 42    | 1904                     | 5250   |
| EF6 / EFO6           | 1.8            | 6    | 1.93                                     | 6.3  | 610        | 160   | 305                                      | 12   | 3470                      | 123   | 5552                     | 15375  |
| EF8 / EFO8           | 2.4            | 8    | 2.59                                     | 8.5  | 1070       | 280   | 610                                      | 24   | 8780                      | 310   | 14048                    | 38750  |
| EF10 / EFO10         | 3.0            | 10   | 3.25                                     | 10.7 | 1670       | 440   | 610                                      | 24   | 17790                     | 628   | 28464                    | 78500  |
| EF12 / EFO12         | 3.6            | 12   | 3.89                                     | 12.8 | 2475       | 655   | 610                                      | 24   | 31220                     | 1103  | 49952                    | 137875 |

\*Increased sump depth may be added to increase sediment storage capacity

\*\* Average density of wet packed sediment in sump = 1.6 kg/L (100 lb/ft³)

| Feature   | Benefit   | Feature Appeals To                                  |
|---|---|---|
| Patent-pending enhanced flow treatment and scour prevention technology  | Superior, verified third-party performance        | Regulator, Specifying & Design Engineer             |
| Third-party verified light liquid capture and retention for EFO version | Proven performance for fuel/oil hotspot locations | Regulator, Specifying & Design Engineer, Site Owner |
| Functions as bend, junction or inlet structure                          | Design flexibility                                | Specifying & Design Engineer                        |
| Minimal drop between inlet and outlet                                   | Site installation ease                            | Contractor  |
| Large diameter outlet riser for inspection and maintenance              | Easy maintenance access from grade                | Maintenance Contractor & Site Owner                 |

### STANDARD STORMCEPTOR EF/EFO DRAWINGS

For standard details, please visit <http://www.imbriumsystems.com/stormwater-treatment-solutions/stormceptor-ef>

### STANDARD STORMCEPTOR EF/EFO SPECIFICATION

For specifications, please visit <http://www.imbriumsystems.com/stormwater-treatment-solutions/stormceptor-ef>

## Stormceptor®EF Sizing Report

### STANDARD PERFORMANCE SPECIFICATION FOR “OIL GRIT SEPARATOR” (OGS) STORMWATER QUALITY TREATMENT DEVICE

#### PART 1 – GENERAL

##### 1.1 WORK INCLUDED

This section specifies requirements for selecting, sizing, and designing an underground Oil Grit Separator (OGS) device for stormwater quality treatment, with third-party testing results and a Statement of Verification in accordance with ISO 14034 Environmental Management – Environmental Technology Verification (ETV).

##### 1.2 REFERENCE STANDARDS & PROCEDURES

ISO 14034:2016 Environmental management – Environmental technology verification (ETV)

Canadian Environmental Technology Verification (ETV) Program’s **Procedure for Laboratory Testing of Oil-Grit Separators**

##### 1.3 SUBMITTALS

1.3.1 All submittals, including sizing reports & shop drawings, shall be submitted upon request with each order to the contractor then forwarded to the Engineer of Record for review and acceptance. Shop drawings shall detail all OGS components, elevations, and sequence of construction.

1.3.2 Alternative devices shall have features identical to or greater than the specified device, including: treatment chamber diameter, treatment chamber wet volume, sediment storage volume, and oil storage volume.

1.3.3 Unless directed otherwise by the Engineer of Record, OGS stormwater quality treatment product substitutions or alternatives submitted within ten days prior to project bid shall not be accepted. All alternatives or substitutions submitted shall be signed and sealed by a local registered Professional Engineer, based on the exact same criteria detailed in Section 3, in entirety, subject to review and approval by the Engineer of Record.

#### PART 2 – PRODUCTS

##### 2.1 OGS POLLUTANT STORAGE

The OGS device shall include a sump for sediment storage, and a protected volume for the capture and storage of petroleum hydrocarbons and buoyant gross pollutants. The minimum sediment & petroleum hydrocarbon storage capacity shall be as follows:

|       |                                     |   |
|-------|-------------------------------------|---|
| 2.1.1 | 4 ft (1219 mm) Diameter OGS Units:  | 1.19 m <sup>3</sup> sediment / 265 L oil    |
|       | 6 ft (1829 mm) Diameter OGS Units:  | 3.48 m <sup>3</sup> sediment / 609 L oil    |
|       | 8 ft (2438 mm) Diameter OGS Units:  | 8.78 m <sup>3</sup> sediment / 1,071 L oil  |
|       | 10 ft (3048 mm) Diameter OGS Units: | 17.78 m <sup>3</sup> sediment / 1,673 L oil |
|       | 12 ft (3657 mm) Diameter OGS Units: | 31.23 m <sup>3</sup> sediment / 2,476 L oil |

#### PART 3 – PERFORMANCE & DESIGN

##### 3.1 GENERAL

The OGS stormwater quality treatment device shall be verified in accordance with ISO 14034:2016 Environmental management – Environmental technology verification (ETV). The OGS stormwater quality treatment device shall

## Stormceptor®EF Sizing Report

remove oil, sediment and gross pollutants from stormwater runoff during frequent wet weather events, and retain these pollutants during less frequent high flow wet weather events below the insert within the OGS for later removal during maintenance. The Manufacturer shall have at least ten (10) years of local experience, history and success in engineering design, manufacturing and production and supply of OGS stormwater quality treatment device systems, acceptable to the Engineer of Record.

### 3.2 SIZING METHODOLOGY

The OGS device shall be engineered, designed and sized to provide stormwater quality treatment based on treating a minimum of 90 percent of the average annual runoff volume and a minimum removal of an annual average 60% of the sediment (TSS) load based on the Particle Size Distribution (PSD) specified in the sizing report for the specified device. Sizing shall be determined using historical rainfall data and a sediment removal performance curve derived from the actual third-party verified laboratory testing data. The OGS device shall also have sufficient annual sediment storage capacity as specified and calculated in Section 2.1.

### 3.3 CANADIAN ETV or ISO 14034 ETV VERIFICATION OF SCOUR TESTING

The OGS device shall have Canadian ETV or ISO 14034 ETV Verification of third-party scour testing conducted in accordance with the Canadian ETV Program's **Procedure for Laboratory Testing of Oil-Grit Separators**.

3.3.1 To be acceptable for on-line installation, the OGS device must demonstrate an average scour test effluent concentration less than 10 mg/L at each surface loading rate tested, up to and including 2600 L/min/m<sup>2</sup>.

### 3.4 LIGHT LIQUID RE-ENTRAINMENT SIMULATION TESTING

The OGS device shall have Canadian ETV or ISO 14034 ETV Verification of completed third-party Light Liquid Re-entrainment Simulation Testing in accordance with the Canadian ETV **Program's Procedure for Laboratory Testing of Oil-Grit Separators**, with results reported within the Canadian ETV or ISO 14034 ETV verification. This re-entrainment testing is conducted with the device pre-loaded with low density polyethylene (LDPE) plastic beads as a surrogate for light liquids such as oil and fuel. Testing is conducted on the same OGS unit tested for sediment removal to assess whether light liquids captured after a spill are effectively retained at high flow rates.

3.4.1 For an OGS device to be an acceptable stormwater treatment device on a site where vehicular traffic occurs and the potential for an oil or fuel spill exists, the OGS device must have reported verified performance results of greater than 99% cumulative retention of LDPE plastic beads for the five specified surface loading rates (ranging 200 L/min/m<sup>2</sup> to 2600 L/min/m<sup>2</sup>) in accordance with the Light Liquid Re-entrainment Simulation Testing within the Canadian ETV Program's **Procedure for Laboratory Testing of Oil-Grit Separators**. However, an OGS device shall not be allowed if the Light Liquid Re-entrainment Simulation Testing was performed with screening components within the OGS device that are effective at retaining the LDPE plastic beads, but would not be expected to retain light liquids such as oil and fuel.



---

## **Appendix D: Sanitary Calculations**

---

# SANITARY FLOW CALCULATION

## ESTIMATED SITE DISCHARGE



**PROJECT:** Columbia Square, Caledon  
**FILE No.:** 21-0012CA  
**DATE:** Dec 2021  
**PREPARED BY:** MP

|                        |                   |
|------------------------|-------------------|
| Site Area              | 3.30 ha           |
| Infiltration Rate      | 0.20 L/s/ha *     |
| Sewage Generation Rate | 302.8 L/cap/day * |

\* Per Region of Peel Criteria

### PROPOSED CONDITION

| Land Use         | Units | Area (ha) | Density (ppu or p/ha) | Population | Avg. Flow (L/s) | Peaking Factor | Peak Flow (L/s) | Infilt. (L/s) | Total Flow (L/s) |
|------------------|-------|-----------|-----------------------|------------|-----------------|----------------|-----------------|---------------|------------------|
| Ph. 1A Townhouse | 24    | 0.72      | 175 p/ha              | 126        | 0.4             | 3.76           | 1.5             | 0.1           | 1.6              |
| Ph. 1B Townhouse | 118   | 0.68      | 175 p/ha              | 119        | 0.4             | 3.76           | 1.5             | 0.3           | 1.8              |
| Ph. 2 Apartment  | 244   | 1.29      | 475 p/ha              | 613        | 2.1             | 3.76           | 7.9             | 0.3           | 8.2              |
| Ph. 3 Apartment  | 159   | 0.61      | 475 p/ha              | 290        | 1.0             | 3.76           | 3.8             | 0.1           | 3.9              |
| Total            | 545   | 3.30      | NA                    | 1148       | 3.9             | 3.76           | 14.7            | 0.8           | 15.5             |

---

## **Appendix E: Water Supply Calculations**

---

PROJECT:  
PROJECT #:  
DATE:

Columbia Square

21-0012CA

07-Jan-22

## WATER DEMAND DESIGN ANALYSIS

### REGION OF PEEL DESIGN CRITERIA

Watermains to be sized based on the greater of:

1. Maximum Day Demand plus Fire Flow or
2. Peak Hour Demand

### Water Demand Design Criteria

|                                   |             |
|-----------------------------------|-------------|
| Average Day Demand - Residential  | 280 L/cap/d |
| Average Day Demand - Commercial   | 300 L/cap/d |
| Maximum Day Factor - Residential  | 2.0         |
| Maximum Day Factor - Commercial   | 1.4         |
| Peak Hour Factor - Res. and Inst. | 3.0         |

### Population Equivalents

|                             |          |
|-----------------------------|----------|
| Townhouse Development       | 175 ppu  |
| Future Mid-Rise Development | 475 ppha |
| Commercial Development      | 50 ppha  |

### Water System Demand

| Land Use                    | Units # | Area<br>(ha) | Population  | Ave. Day<br>Flow<br>(L/s) | Max Day<br>Demand<br>(L/s) | Max Hour<br>Demand<br>(L/s) | Fire Flow<br>Demand<br>(L/s) | Max Day +<br>Fire Flow<br>(L/s) |
|-----------------------------|---------|--------------|-------------|---------------------------|----------------------------|-----------------------------|------------------------------|---------------------------------|
| <b>PHASE 1A</b>             |         |              |             |                           |                            |                             |                              |                                 |
| Townhouses                  | 24      | 0.720        | 126         | 0.41                      | 0.82                       | 1.23                        | 216.67                       | 217.48                          |
| <b>PHASE 1B</b>             |         |              |             |                           |                            |                             |                              |                                 |
| Townhouses                  | 118     | 0.680        | 119         | 0.39                      | 0.77                       | 1.16                        | 150.00                       | 150.77                          |
| <b>PHASE 2</b>              |         |              |             |                           |                            |                             |                              |                                 |
| Mixed-Use Comm./Residential | 244     | 1.290        | 613         | 1.99                      | 3.97                       | 5.96                        | 250.00                       | 253.97                          |
| <b>PHASE 3</b>              |         |              |             |                           |                            |                             |                              |                                 |
| Retirement Residence        | 159     | 0.610        | 290         | 0.94                      | 1.88                       | 2.82                        | 116.67                       | 118.54                          |
| <b>TOTAL</b>                |         | <b>3.300</b> | <b>1148</b> | <b>3.72</b>               | <b>7.44</b>                | <b>11.16</b>                | <b>250.00</b>                | <b>257.44</b>                   |

### Fire Flow Demand

|                                |            |
|--------------------------------|------------|
|                                | Fire Flow  |
| FUS Calculation                | 250.00 L/s |
| Maximum Day Demand + Fire Flow | 257.44 L/s |
| Peak Hour Demand Flow          | 11.16 L/s  |

FIRE FLOW CALCULATION

PROJECT: Columbia Square  
FILE No.: 21-0012CA  
DATE: January 2022  
PREPARED BY: MP

Calculation of required fire flow is based on the Fire Underwriters Survey (FUS), Water Supply for Fire Protection publication, 1999.

F = 220C√A

Where: F = Required fire flow (L/min.)

C = Coefficient related to the type of construction

- 1.5 for wood frame construction (combustible)
- 1.0 for ordinary construction (brick/masonry walls, with combustible floor & interior)
- 0.8 for non-combustible construction (unprotected metal structural components, masonry or metal walls)
- 0.6 for fire-resistive construction (fully protected frame, floors, roof)

A = Total floor area (m²)

Includes all storeys, but excluding basements at least 50% below grade.

For fire-resistive buildings, consider the 2 largest adjoining floors plus 50% of each of any floors immediately above up to 8, when vertical openings are inadequately protected.

If the vertical openings and exterior vertical communications are properly protected (one hour rating), consider only the area of the largest floor plus 25% of eachh of the 2 immediately adjoining floors.

Adjustments to the calculated fire flow can be made based on occupancy, sprinkler protection and exposure to other structures. The table below summarizes the adjustments made to the basic fire flow demand.

| Building   | Area "A" | C | 1              |       | 2         |                              | 3         |                              | 4        |                              | Final Adjusted          |                           |       |
|------------|----------|---|----------------|-------|-----------|------------------------------|-----------|------------------------------|----------|------------------------------|-------------------------|---------------------------|-------|
|            |          |   | Base Fire Flow |       | Occupancy |                              | Sprinkler |                              | Exposure |                              | Fire Flow               |                           |       |
|            | (m2)     |   | (L/min)        | (L/s) | %         | Fire Flow Adjustment (L/min) | %         | Fire Flow Adjustment (L/min) | %        | Fire Flow Adjustment (L/min) | Final Fire Flow (L/min) | Rounded Fire Flow (L/min) | (L/s) |
| PHASE 1A   |          |   |                |       |           |                              |           |                              |          |                              |                         |                           |       |
| West Block | 833.4    | 1 | 6351           | 105.9 | -15       | -953                         | 0         | 0                            | 40%      | 2540                         | 7939                    | 8000                      | 133   |
| Mid Block  | 779.55   | 1 | 6142           | 102.4 | -15       | -921                         | 0         | 0                            | 55%      | 3378                         | 8599                    | 9000                      | 150   |
| East Block | 1728     | 1 | 9145           | 152.4 | -15       | -1372                        | 0         | 0                            | 55%      | 5030                         | 12803                   | 13000                     | 217   |
| PHASE 1B   |          |   |                |       |           |                              |           |                              |          |                              |                         |                           |       |
| Northwest  | 840      | 1 | 6376           | 106.3 | -15       | -956                         | 0         | 0                            | 50%      | 3188                         | 8608                    | 9000                      | 150   |
| North      | 840      | 1 | 6376           | 106.3 | -15       | -956                         | 0         | 0                            | 60%      | 3826                         | 9245                    | 9000                      | 150   |
| Northeast  | 840      | 1 | 6376           | 106.3 | -15       | -956                         | 0         | 0                            | 60%      | 3826                         | 9245                    | 9000                      | 150   |
| Southwest  | 840      | 1 | 6376           | 106.3 | -15       | -956                         | 0         | 0                            | 45%      | 2869                         | 8289                    | 8000                      | 133   |
| South      | 840      | 1 | 6376           | 106.3 | -15       | -956                         | 0         | 0                            | 45%      | 2869                         | 8289                    | 8000                      | 133   |
| Southeast  | 840      | 1 | 6376           | 106.3 | -15       | -956                         | 0         | 0                            | 50%      | 3188                         | 8608                    | 9000                      | 150   |
| PHASE 2    |          |   |                |       |           |                              |           |                              |          |                              |                         |                           |       |
| Building   | 5410.5   | 1 | 16182          | 269.7 | -15       | -2427                        | -30       | -4855                        | 35%      | 5664                         | 14564                   | 15000                     | 250   |
| PHASE 3    |          |   |                |       |           |                              |           |                              |          |                              |                         |                           |       |
| Building   | 2467.5   | 1 | 10928          | 182.1 | -15       | -1639                        | -30       | -3278                        | 10%      | 1093                         | 7103                    | 7000                      | 117   |
|            |          |   |                |       |           |                              |           |                              |          |                              |                         |                           |       |
|            |          |   |                |       |           |                              |           |                              |          |                              |                         |                           |       |
|            |          |   |                |       |           |                              |           |                              |          |                              |                         |                           |       |
|            |          |   |                |       |           |                              |           |                              |          |                              |                         |                           |       |
|            |          |   |                |       |           |                              |           |                              |          |                              |                         |                           |       |

GFA for townhouse blocks estimated based on site plan prepared by MBTW WAI dated March 4, 2021



| (2) Occupancy       | (3) Spinkler  | (4) Exposure                               |
|---------------------|---|--|
| Non-Combustible     | It is assumed Phases 2 and 3 will have a sprinkler system | 0 to 3 m                                   |
| Limited Combustible |   | 3.1 to 10 m                                |
| Combustible         |   | 10.1 to 20 m                               |
| Free Burning        |   | 20.1 to 30 m                               |
| Rapid Burning       |   | 30.1 to 45 m                               |
|                     |   | > 45 m                                     |
|                     |   | Calculate for all sides and all buildings. |

---

## **Appendix F: Functional Engineering Drawings**

---





- LEGEND**
- DENOTES VALVE AND CHAMBER
  - DENOTES VALVE AND BOX
  - ◇ DENOTES HYDRANT
  - AD □ DENOTES AREA DRAIN
  - CB □ DENOTES SINGLE CATCHBASIN
  - DCB □ DENOTES DOUBLE CATCHBASIN
  - DENOTES SANITARY MANHOLE
  - DENOTES STORM MANHOLE
  - ▼ DENOTES EXTERIOR ENTRANCE
  - ① DENOTES PIPE CROSSING
  - DENOTES PROPOSED BUILDING
  - DENOTES PROPOSED BUILDING STRUCTURE BELOW GRADE
  - DENOTES DOUBLE CATCHBASIN
  - DENOTES STORMWATER STORAGE TANK

**NOT FOR CONSTRUCTION**  
THE DESIGN PRESENTED ON THIS DRAWING IS PRELIMINARY, AND HAS BEEN PREPARED IN SUPPORT OF A FUNCTIONAL SERVICING STUDY FOR THE SUBJECT SITE. THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION.

| DRAWING LIST |  |  |
|--------------|--|--|
| FS-01        | FUNCTIONAL SERVICING PLAN                  |  |
| FG-01        | FUNCTIONAL GRADING PLAN                    |  |
| FSC-1        | FUNCTIONAL EROSION & SEDIMENT CONTROL PLAN |  |
| D-01         | DETAILS                                    |  |

| SUBMISSION HISTORY |                               |             |
|--------------------|-------------------------------|-------------|
| No.                | ISSUED FOR                    | DATE        |
| 1.                 | ISSUED FOR ZBA 1ST SUBMISSION | JAN.10.2022 |

| REVISIONS |             |         |
|-----------|-------------|---------|
| No.       | DESCRIPTION | BY DATE |
|           |             |         |
|           |             |         |
|           |             |         |

**BENCHMARK NOTE:**  
ELEVATIONS ARE GEODETIC AND ARE REFERRED TO THE VERTICAL BENCH MARK NUMBER 00819758060 HAVING AN ORTHOMETRIC ELEVATION OF 269.667 METRES. ELEVATIONS ARE REFERENCED TO THE CANADIAN GEODETIC VERTICAL DATUM OF 1928, 1978 ADJUSTMENT (CGVD-1928/1978).  
TABLET IS SET HORIZONTALLY IN THE NORTHWEST FACE OF A CONCRETE SILO, BELOW STEEL RING LADDER, 49cm ABOVE GRADE. SILO LOCATED ON THE EAST SIDE OF HWY 50, 3.3km NORTH OF JCT OF HWY 50 AND KING STREET IN THE TOWN OF CALEDON (BOLTON), 1.0km SOUTH OF ALBION SIDEROAD 15 AND 68cm EAST OF CENTERLINE OF HWY 50.

CONSULTANT

MUNICIPAL APPROVAL

urbanworks  
ENGINEERING CORPORATION  
Toronto, Ontario, CANADA | Tel: 416-503-4500  
e: general@urbanworkseng.com | www.urbanworkseng.com

**COLUMBIA SQUARE**  
14245 HIGHWAY 50, BOLTON, ON.



Region of Peel  
working with you

TOWN OF CALEDON



| FUNCTIONAL SERVICING PLAN |                   |          |
|---------------------------|-------------------|----------|
| TOWN FILE:                | PROJECT No.       |          |
| REGION FILE:              | 21-0012CA         |          |
| DATE: JAN. 10, 2022       | DESIGNED BY: T.D. | DWG. No. |
| SCALE: 1:500              | DRAWN BY: T.D.    | FS-01    |
|                           | CHECKED BY: M.M.  |          |





- LEGEND**
- DENOTES VALVE AND CHAMBER
  - ⊕ DENOTES VALVE AND BOX
  - ⊙ DENOTES HYDRANT
  - AD □ DENOTES AREA DRAIN
  - CB □ DENOTES SINGLE CATCHBASIN
  - DCB □ DENOTES DOUBLE CATCHBASIN
  - DENOTES SANITARY MANHOLE
  - DENOTES STORM MANHOLE
  - ▼ DENOTES EXTERIOR ENTRANCE
  - ▭ DENOTES PROPOSED BUILDING
  - ▭ DENOTES PROPOSED BUILDING STRUCTURE BELOW GRADE
  - 189.52 DENOTES PROPOSED ELEVATION
  - 190.14 DENOTES EXISTING ELEVATION
  - [189.52] DENOTES FUTURE ELEVATION
  - 188.5 DENOTES EXISTING CONTOUR
  - ▭ DENOTES OVERLAND FLOW ROUTE

**NOT FOR CONSTRUCTION**  
THE DESIGN PRESENTED ON THIS DRAWING IS PRELIMINARY, AND HAS BEEN PREPARED IN SUPPORT OF A FUNCTIONAL SERVICING STUDY FOR THE SUBJECT SITE. THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION.

| DRAWING LIST |  |
|--------------|--|
| FS-01        | FUNCTIONAL SERVICING PLAN                  |
| FG-01        | FUNCTIONAL GRADING PLAN                    |
| FSC-1        | FUNCTIONAL EROSION & SEDIMENT CONTROL PLAN |
| D-01         | DETAILS                                    |

| SUBMISSION HISTORY |                               |             |
|--------------------|-------------------------------|-------------|
| No.                | ISSUED FOR                    | DATE        |
| 1.                 | ISSUED FOR ZBA 1ST SUBMISSION | JAN.10,2022 |

| REVISIONS |             |    |      |
|-----------|-------------|----|------|
| No.       | DESCRIPTION | BY | DATE |
|           |             |    |      |
|           |             |    |      |
|           |             |    |      |

**BENCHMARK NOTE:**  
ELEVATIONS ARE GEODETIC AND ARE REFERRED TO THE VERTICAL BENCH MARK NUMBER 00819758060 HAVING AN ORTHOMETRIC ELEVATION OF 269.667 METRES. ELEVATIONS ARE REFERENCED TO THE CANADIAN GEODETIC VERTICAL DATUM OF 1928, 1978 ADJUSTMENT (CGVD-1928-1978).  
TABLET IS SET HORIZONTALLY IN THE NORTHWEST FACE OF A CONCRETE SILO, BELOW STEEL RING LADDER, 49cm ABOVE GRADE. SILO LOCATED ON THE EAST SIDE OF HWY 50, 3.3km NORTH OF JCT OF HWY 50 AND KING STREET IN THE TOWN OF CALEDON (BOLTON), 1.0km SOUTH OF ALBION SIDEROAD 15 AND 68cm EAST OF CENTERLINE OF HWY 50.

CONSULTANT

MUNICIPAL APPROVAL

**urbanworks**  
ENGINEERING CORPORATION  
Toronto, Ontario, CANADA | tel. 416-503-4500  
e. general@urbanworksgroup.com | w. www.urbanworksgroup.com

**COLUMBIA SQUARE**  
14245 HIGHWAY 50, BOLTON, ON.

**Region of Peel**  
working with you

**TOWN OF CALEDON**

SCALE 0 5 10 15 20 25 30 35 40 45 50m

**FUNCTIONAL GRADING PLAN**

|                     |                   |                              |  |
|---------------------|-------------------|------------------------------|--|
| TOWN FILE:          |                   | PROJECT No.<br><br>21-0012CA |  |
| REGION FILE:        |                   |                              |  |
| DATE: JAN. 10, 2022 | DESIGNED BY: T.D. | DWG. No.<br><br>FG-01        |  |
| SCALE: 1:500        | DRAWN BY: T.D.    |                              |  |
|                     | CHECKED BY: M.M.  |                              |  |