## **Application Submitted**

	Site Plan Control Secondary Plan	OP/Zoning E	By-law Amendment	Draft F	Plan of Subdivision	Block Plan
Office	Use Only					
Munici	pality:	Brampton	Caledon	Mississauga		
Date R	eceived:	Planner:			Application No.:	
Is this I	HDA revised from an ear	lier submission?	Yes	No		
Prop	erty and Applican	t				
Addres	ss of Subject Land (Stree	t Number/Name):				
	ered Owner:			E-mail:		
Gross I	sal Description				nits:	
Projec	<b>t Summary</b> (describe ho	ow the project contr	ibutes to a nealthy com	imunity)		



# PEEL HEALTHY DEVELOPMENT ASSESSMENT (LARGE-SCALE)

Please indicate where and how a standard is met or exceeded in the Demonstration of Standard column with reference to a policy, plan, map or illustration of some kind in the Document/Policy Reference column. Please also tabulate points in the Score column based on whether the development proposal meets or does not meet a community design standard. For further instruction, refer to "How to Use this User Guide" on pages 2 and 3.

Standard	Demonstration of Standard	Document/Policy Reference	Potential Score	Actual Score
DENSITY		Reference	Score	Score
<ol> <li>All development on Designated <i>Greenfield Areas</i> shall achieve a minimum overall density target as prescribed by the Regional Official Plan in policies 5.5.4.2.1 and 5.5.4.2.2.</li> </ol>				
Where the local municipality has established higher density targets, these higher targets will apply.			- 5	
2. All development in Designated Urban Growth Centres in the Region of Peel (i.e., Downtown Brampton and Mississauga City Centre) achieves a minimum overall density target of 200 people and jobs per hectare.				
Where the local municipality has established higher density targets, these higher targets will apply.				

	Standard	Demonstration of Standard	Document/Policy Reference	Potential Score	Actual score
SE	RVICE PROXIMITY				
	ansit				
3.	At least 50% of the development's proposed dwelling units are situated within 200m of a planned or existing transit stop.			2	
4.	Areas within 400m of a Higher Order Transit stop are developed to meet Major Transit Station Area density targets.			1	
	Access to transit from the proposed development is safe, attractive and direct for pedestrians.			n/a	
	ighbourhood Community and Ret	ail Services			
6.	At least 75% of the proposed dwelling units are situated within 800m of three or more of the following planned or existing neighbourhood public services: • childcare facility • community garden • hospital or health clinic • public library • place of worship • adult/senior care facility • social service facility • performance or cultural space • post office • recreation centre			2	
7.	100% of the proposed dwelling units are within 800m of an existing or planned			1	

	Standard	Demonstration of Standard	Document/Policy Reference	Potential Score	Actual score
e	lementary school.		nererence	JUIC	5000
	00% of the proposed				
	welling units are within				
	.6km of an existing or			1	
	lanned secondary school.				
	t least 90% of the proposed				
	welling units are situated				
	vithin 400m of a playing field,			2	
	ark, square or natural open				
-	pace.				
	t least 75% of the proposed				
	welling units are within 800m				
	f 5,000m <sup>2</sup> of personal service				
	nd commercial retail space,			2	
	omprising a mix of uses such			2	
	s a grocery store, pharmacy,				
b	ank, coffee, shop, restaurant,				
d	ry cleaner and hair salon.				
11. C	onvenience commercial uses				
aı	re present in key locations,				
in	ncluding greyfield areas,			2	
in	ntensification areas and				
СС	orridors and greenfield areas.				
Emplo	oyment				
12. TI	he development is within				
1(	0km (i.e., a 30 minute transit				
tr	ip) of an existing or planned			2	
ei	mployment centre or urban				
Ce	entre.				
LAND	USE MIX				
13. Eı	<i>mployment lands</i> include				
	mall scale amenity retail and				
	ervices, are serviced by transit			2	
	nd have infrastructure which			2	
ei	ncourages pedestrian and				
	yclist movement.				
	combination, the following			2	
	ousing type groups make up			2	

Standard	Demonstration of Standard	Document/Policy Reference	Potential Score	Actual score
at least 50% of the total units:				
<ul> <li>townhouses and multiplex</li> </ul>				
<ul> <li>apartment buildings</li> </ul>				
15. The proposed development				
includes special housing types,				
such as senior's housing, long			1	
term care facilities and			I	
supportive or affordable				
housing.				
16. Live-work units and other				
employment-related uses				
compatible with residential			2	
uses are included in the			_	
proposed development.				
17. Retail uses on the ground floor				
are provided in multi-unit and				
mixed-use buildings.			1	
STREET CONNECTIVITY				
18. Infill development increases				
opportunities for street and				
pedestrian linkages and				
connectivity.				
19. In designated Greenfield Areas,				
street networks and off-road			1	
paths:				
<ul> <li>are multi-modal to provide</li> </ul>				
choice to pedestrians and				
cyclists; and				
make clear connections to				
existing routes and facilities.				
20. Cul-de-sacs, crescent streets				
and loop roads are not utilized			2	
unless they are located near				
significant infrastructure,				

Standard	Demonstration of Standard	Document/Policy Reference	Potential Score	Actual score
including highways and				
railways, or near natural				
features.				
21. Reverse frontage streets are				
not utilized.				
			1	
22. Residential blocks in the				
proposed development do not			2	
exceed 80x180m in size.			3	
23. Intersections are frequent				
(75/sq.km), with street blocks			2	
decreasing in size as density			3	
increases.				
24. Sidewalks, bike lanes and				
multi-use paths connect to				
street networks, community			n/a	
amenities and transportation				
nodes.				
STREETSCAPE CHARACTERISTICS				
Pedestrian Amenities				
25. Neighbourhood public and				
retail services are located				
linearly along major roads to				
promote a main street			2	
environment, and are focused				
within community and mixed				
use nodes.				
26. All streets in low-density				
residential areas have				
sidewalks on each side that are				
at least 1.5m wide.			1	
All streets in medium- and			I	
high-density residential				
neighbourhoods, mixed-use				
areas and commercial areas				

Standard	Demonstration of Standard	Document/Policy	Potential	Actual
		Reference	Score	score
have sidewalks on each side				
that are at least 2 m wide.				
27. A variety of street trees that				
are hardy, resilient, and low				
maintenance are planted at			1	
regular intervals (as specified			·	
by the municipality) adjacent				
to all streets.				
28. All transit stations, major				
transit stations and major				
pedestrian routes have:				
<ul> <li>weather protection</li> </ul>				
seating			1	
waste baskets				
lighting				
route information				
bicycle parking				
Cycling Amenities				
29. A connected and destination-				
oriented bikeway network is				
provided throughout the				
community, including a variety				
of on- and off-street bikeway				
facilities. These provide an				
appropriate degree of				
separation from motorized				
traffic, taking into account the				
speed and volume of traffic on				
the street. These on-street			1	
bikeway facilities must include:				
<ul> <li>bicycle lanes</li> </ul>				
sharrows				
<ul> <li>signed routes</li> </ul>				
<ul> <li>multi-use paths on the</li> </ul>				
boulevard				
DOUIEValu				
Where there is a local Bicycle				
Plan, the bikeway network				
Fian, the Dikeway network				

Standard	Demonstration of Standard	Document/Policy Reference	Potential Score	Actual score
proposed in the Plan is				50010
implemented in the				
development area, and				
opportunities to enhance, or				
connect, the proposed				
bikeway network are				
identified.				
30. 90% of the residential dwelling				
units are within 400m of a				
continuous and connected			1	
bike network.				
Lighting				
31. Residential and commercial				
streets in medium- to high-				
density neighbourhoods have			1	
pedestrian-scaled lighting and				
are limited to a height of 4.6m.				
32. Lighting and light standards in				
public outdoor areas, such as				
pedestrian walkways, plazas,				
parks, play lots and parking			1	
areas, relate to the pedestrian				
and are limited to a height of				
4.6m.				
Traffic Calming				
33. In greenfield development, or				
where new streets are				
introduced through infill				
(re)development, traffic				
calming is achieved by using				
any of, but not limited to, the				
following:			3	
minimum traffic lane				
widths				
minimum number of traffic				
lanes in the roadway				
Pedestrian-priority streets,				
woonerfs or home-zones				

Standard	Demonstration of Standard	Document/Policy Reference	Potential Score	Actual score
(i.e., the speed limit is				
under 15km/hr and				
vehicles must yield to				
pedestrians and cyclists)				
34. Traffic calming elements are				
designed to increase comfort				
and safety for means of active				
transportation, so as not to			n/a	
unduly create hazards or				
obstacles for pedestrians or				
cyclists.				
EFFICIENT PARKING				
35. Provide reduced automobile				
parking ratios for:				
<ul> <li>buildings and other facilities</li> </ul>				
within 400m of a higher			1	
order transit stops; and,			I	
• apartments/condominiums				
offering car share parking				
spaces.				
36. Efficient use of parking is				
promoted by identifying				
systems for sharing parking				
spaces by two or more user				
groups at different times of the			1	
day or week (e.g., weekday use				
by office staff and				
evening/weekend use by				
restaurant clientele).				
37. Provide unbundled parking for				
50% of multi-family dwelling			2	
units within 400m of a higher-			2	
order transit stop.				
38. 50% or more of residential				
dwelling units provide access				
to parking via rear alleys or			2	
laneways, with no parking in				
their front setbacks.				

Standard	Demonstration of Standard	Document/Policy Reference	Potential Score	Actual score
39. For multi-storey residential				
dwelling units, institutional				
and employment uses, parking			2	
is located away from the street			2	
to the rear or to the side, or is				
located underground.				
40. Where surface parking is				
provided, it is designed to				
minimize negative aesthetic				
and environmental impacts.				
This can be achieved by				
incorporating the following				
into the parking lot design:				
<ul> <li>pedestrian access,</li> </ul>			2	
connectivity and circulation				
<ul> <li>tree planting</li> </ul>				
landscaping				
<ul> <li>stormwater management</li> </ul>				
<ul> <li>porous/permeable surfaces</li> </ul>				
<ul> <li>light-coloured materials</li> </ul>				
instead of black asphalt				

# HEALTHY DEVELOPMENT ASSESSMENT SCORECARD

/ /5

/ /2 /1 N/A /2 /1 /1

/2 /2 /2 /2

/ /2 /2 /1

/2 /1

/ /1

# DENSITY

Density targe	ts
(Tick correct box)	Greenfield targets

Urban Growth Centre targets

## **SERVICE PROXIMITY**

Transit proximity
Major Transit Station Area targets
Safe & comfortable transit access
Proximity to neighbourhood public services
Proximity to elementary school
Proximity to secondary school
Proximity to park, square or natural space
Proximity to commercial retail
Convenience commercial in key locations
Proximity to employment or urban centre

# LAND USE MIX

Employment Lands	
Housing diversity	
Special Housing	
Live-Work units and other employment uses	
Retail uses on ground floor	

#### **STREET CONNECTIVITY**

Improv	/ed connectivity
	Infill development
	C E. L. I. I

Greenfield development	
Non-grid streets avoided	/2
Reverse-frontage streets avoided	/1
Small residential blocks	/3
Frequent intersections	/3
Active transportation connectivity	N/A

#### **STREETSCAPE CHARACTERISTICS**

Linear and nodal commercial development	/2
Sidewalks	/1
Street trees	/1
Transit Station amenities	/1
Connected bike network	/1
Proximity to bike network	/1
Lighting on residential/commercial streets	/1
Public outdoor lighting	/1
Traffic calming	/3
Traffic calming enhances comfort and safety	N/A

# **EFFICIENT PARKING**

Provide reduced parking ratios	/1
Identify systems for shared parking spaces	/1
Unbundled parking	/2
Parking location (single-storey residential)	/2
Parking location (other)	/2
Above-ground parking design	/2

### **TOTAL\*:**

GOLD:	80-100%
SILVER:	70-79%
BRONZE:	60-69%
PASS:	50-59%

\*Should certain standards not apply, the total score will be reduced accordingly.

#### HEALTHY DEVELOPMENT ASSESSMENT (Large Scale)

#### **APPENDIX** A

**Standard 22 -** Some of the blocks on the plan are larger than 80x180m. The lengths are as follows (all measurements property line to property line):

- Block bounded by Airport Road, Laneway 1, Block 565, St. A = 243.1 m
- Block bounded by Sts. N, M, L, A = 185.6 m
- Block bounded by Sts. N, L, K, A (south) = 185.4 m
- Block bounded by Sts. A, B, C (two sides) = 232.9 m
- Block bounded by Sts. A, S, Q, P = 217.3 m
- Block bounded Sts. N, H, F, Laneways 4 & 5 = 204.1 m
- Block bounded by Sts. E, D (three sides) = 183.8 m

**Standard 23** – The blocks of laneway dwellings interior to the site are on shorter blocks than those facing Airport Road. This provides an appropriate transition to the eastern portion of the site.

## Appendix B



Figure 1 - Public Services Within 800m of Proposed Development

#### Appendix **B**



Figure 2 - Elementary and High Schools Within 800m and 1600m of Proposed Development

## Appendix B



Figure 3 - Commercial Retail Space Within 800m Radius of Proposed Development