



**NOTES:**

1. PROVIDE MIN. 15m SET BACK FROM RESIDENTIAL PROPERTY LINE.
2. PROVIDE MIN. 10m SET BACK FROM ALL ROAD ROW PROPERTY LIMITS.
3. PLAY OUT ZONE TO BE CLEAR OF ANY PHYSICAL ENCROACHMENTS.
4. FOR ALL ASPHALT REFER TO TOWN STD 901. ASPHALT SURFACE TO BE INSTALLED IN TWO LIFTS.
5. FOR BASKET BALL POST & NET ASSEMBLY SEE TOWN STD. No. 1005.
6. SEE ELECTRICAL DRAWINGS FOR LIGHTING LAYOUT.
7. PAINT TO BE SUITABLE FOR ASPHALT SURFACES AS PER O.P.S.S. 710.
8. ALL DIMENSIONS ARE IN MILLIMETERS
9. PROVIDE MAX. 1% CROSS SLOPE FROM LONGITUDINAL HIGH POINT RIDGE ALONG THE CENTER OF THE COURT.
10. PROVIDE MAX 2% SLOPE IN PLAY OUT ZONE.
11. HOOP SPECIFICATIONS AND INSTALLATION AS PER BLUE IMP ULTIMATE
12. ALL COURT LINES TO BE 75mm WIDE AND WHITE.
13. ALL DIMENSIONS IN METERS.
14. REFER TO TOWN OF CALEDON STD No. 1108 FOR BENCH NODE LAYOUT.

TOWN OF CALEDON						APR'D: B.B.	DATE: AUGUST 17
<b>BASKETBALL FULL COURT LAYOUT</b>						DRAWN: B.M.	SCALE: N.T.S.
	NO.	REVISION	APR'D	DATE	<b>STANDARD No. 1003</b>		