



NOTES:

1. UTILITY CORRIDOR TO HAVE A MINIMUM COVER OF 0.9m.
2. WATERMAIN TO HAVE MINIMUM COVER OF 1.7m.
3. THE FOLLOWING IS A MINIMUM ROAD BASE AND WILL REQUIRE A SOILS REPORT VERIFICATION
 40mm HL3
 65mm HL8
 150mm GRANULAR "A"
 300mm GRANULAR "B"
4. THE BOULEVARDS REQUIRE A MINIMUM OF 300mm OF TOPSOIL AND NURSERY SOD

5. TREES TO BE PLACED IN LOCATIONS PER APPROVED LANDSCAPE PLAN
6. STREETLIGHT FIXTURE PER APPROVED TOWN STANDARD.
7. ON A CRESCENT THE WATERMAIN SHALL BE PLACED ON THE OUTSIDE.
8. FULL LENGTH MINIMUM 100MM DIA.SUB-DRAINS C/W FILTERCLOTH SHALL BE INSTALLED TO TOWN OF CALEDON STANDARD NO. 218.
9. SUB-GRADE SHALL BE COMPACTED TO A MINIMUM 95% OF S.P.D. AT OPTIMUM MOISTURE CONTENT.
10. WHERE POSSIBLE MANHOLE LIDS TO BE LOCATED OUT OF TIRE LANE OF TRAFFIC.
11. ESTATE RESIDENTIAL 4.0 METERS LANE WIDTH.

TOWN OF CALEDON 20.0m LOCAL URBAN/RURAL 9.3m ROADWAY (8.7m PAVEMENT)	5	TEXT AND SLOPE REVISIONS	JULY 19	APR'D: C.C.	DATE: 19/01/00
	4	DIMENSION AND TEXT REVISION	JAN. 09		
	3	DIMENSION, LAYOUT REVISION	JULY 08	DRAWN: BJM	SCALE: N.T.S.
	2	DIMENSION EDIT, STD No. 201 NOW 203	JUNE 08		
	1	OFFSETS	APRIL 08	STANDARD No. 203	
NO.	REVISION	APR'D	DATE		