



NOTES:

1. 125 mm (5 in.) TOP DIAM. PRESSURE-TREATED WOOD POSTS, OR COMMERCIAL STEEL POSTS, FOR CATTLE AND HORSES USE 2400 mm (8 ft) TOTAL POST LENGTH FOR SHEEP AND SWINE USE 2100 mm (7 ft) TOTAL POST LENGTH.
2. CORNER AND BRACE POSTS, 150 mm (6 in.) TOP DIAM.

3. 100 mm (4 in.) N. DIAM. BRACE RIAL, NOTCHED AND SPIKED INTO 2.
4. 4 mm (No. 9) BRACE WIRE, TWIST AT TWO LOCATIONS TO TIGHTEN.
5. START FENCING AT CORNER POSTS
6. PAGE WIRE FENCING (SEE MANUFACTURER'S SPECIFICATIONS) FOR CATTLE AND HORSES USE 1050-1200 mm (42-48 in.) HIGH FOR SHEEP

7. OPTIONAL BARBED WIRE TOP STRAND, AT THE DISCRETION OF THE TOWN.
8. CORNER - AND END-POST ANCHORS, WIRED AND SPIKED TO POST.
9. ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED.

TOWN OF CALEDON						APR'D:	DATE: JULY 17
PAGE WIRE FENCING DETAIL						DRAWN:	SCALE: N.T.S.
	NO.	REVISION	APR'D	DATE	STANDARD No. 603		