



ELEVATION VIEW

PLAN VIEW

NOTE:

1. ALL FENCE POSTS TO BE BLACK POLYETHYLENE COATED.
2. ALL PIPE WEIGHTS TO BE SCHEDULE 40.
3. CONCRETE 32MPa MIN. AFTER 28 DAYS.
4. ALL JOINTS TO BE WELDED. WELDING SHALL CONFORM TO THE LATEST ISSUE OF C.S.A. SPECIFICATIONS W59.
5. HINGE PINS TO BE STAINLESS STEEL.
6. GATE TO BE MANUFACTURED AND HOT DIP GALVANIZED.
7. CONTRACTOR TO PADLOCK GATE IMMEDIATELY FOLLOWING INSTALLATION. KEYS TO BE PROVIDED TO TOWN UPON AWARD OF SUBSTANTIAL COMPLETION.
8. ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED.
9. 3M BRAND (OR APPROVED EQUAL) REFLECTIVE GATE ARM MARKINGS, ALTERNATING RED AND WHITE DIAMOND GRADE - 50mm WIDTH (ALONG TOP RAIL).
10. MINIMUM 6.0m WIDTH REQUIRED FOR EMERGENCY ACCESS.

TOWN OF CALEDON					APR'D: C.C.	DATE: MARCH 08
WALKWAY P-GATE	3	TEXT AND DRAWING REVISION		MAY 19	DRAWN: B.B.	SCALE: N.T.S.
	2	STANDARD No. 605 NOW 608		JUNE 08	STANDARD No. 608	
	1	STANDARD No. 930 NOW 605		JUNE 08		
	NO.	REVISION		APR'D	DATE	