



**NOTES:**

1. NOISE ATTENUATION BARRIER TO BE AS PER TOWN OF CALEDON STANDARD No. 614, 615, 616 & 617.
2. BERM FILL MATERIAL TO BE COMPACTED TO 98% S.P.D.
3. BERM SLOPES TO BE SODDED (INCLUDING "PEGGING") WITH 300mm DEPTH OF TOPSOIL.
4. FENCE TO BE LOCATED ON PRIVATE PROPERTY, AND NO PART OF BERM IS TO BE WITHIN THE MUNICIPAL R.O.W.

|   |     |  |       |          |                         |               |
|---|-----|--|-------|----------|-------------------------|---------------|
| TOWN OF CALEDON                               |     |  |       |          | APR'D: C.C.             | DATE: 2007/06 |
| <b>NOISE ATTENUATION<br/>BARRIER AND BERM</b> | 3   | STANDARD No. 610 NOW 613, TEXT EDIT  |       | JAN 18   | DRAWN:                  | SCALE: NTS    |
|   | 2   | NOTE EDIT, S.P.D. CORRECTION, TOPSOIL CORRECTION<br>STANDARD No. 931 NOW 610 |       | JUNE 08  |                         |               |
|   | 1   | TOP OF BERM CORRECTION, ADD NOTE 4   |       | MARCH 08 | <b>STANDARD No. 613</b> |               |
|   | NO. | REVISION   | APR'D | DATE     |                         |               |