



NAILING TABLE			
PRIMARY MEMBER	SECONDARY MEMBER	CONNECTOR TYPE	COMMENTS
1. VERTICAL BEAM	HSS POST	3" SST TB147SS SCREW	2 @ EACH END + 5 IN A STAGGERED PATTERN ALONG BOARD (EVENLY SPACED)
2. HORIZONTAL RAILS	VERTICAL BEAM	SST FB26 FENCE BRACKET	NAILED AS PER MANUFACTURERS REQUIREMENTS
	SKIRT RAIL	3" NAILS	2 @ ENDS + 1 EVERY 300
3. SKIRT RAIL	VERTICAL BEAM	3" NAILS	2 @ EACH POST
4. T. & G. FENCE BOARDS	HORIZONTAL RAILS	3" NAILS	3 @ EACH END - AT LEAST 1 INTO EACH RAIL
5. VERTICAL SPACER	VERTICAL BEAM	3" NAIL	4 SPACED ALONG HEIGHT
6. VERTICAL CLADDING	VERTICAL BEAM	3" NAIL	2 @ EACH END + 5 IN A STAGGERED PATTERN ALONG BOARD (EVENLY SPACED)
	VERTICAL SPACER	3" NAIL	3 ALONG HEIGHT

CAP DETAIL
SCALE 1:2

TOWN OF CALEDON				APR'D: R.G	DATE: JULY 17
ACOUSTIC FENCE DETAIL				DRAWN: B.M	SCALE: N.T.S.
				1	NAILING TABLE TEXT REV.
NO.	REVISION	APR'D	DATE	STANDARD No. 617	