

GENERAL NOTES - LANDSCAPING

NOTE 1

DEPICTED ON THIS PLAN ARE THE SPECIES AND THE APPROXIMATE LOCATION OF STREET TREE. ONCE DRIVEWAYS, UTILITIES AND LIGHT STANDARDS HAVE BEEN INSTALLED, THE EXACT LOCATION OF STREET TREES WILL BE DETERMINED ON SITE BY THE LANDSCAPE CONSULTANT AND APPROVED BY THE MUNICIPALITY PRIOR TO PLANTING.

NOTE 2

MINIMUM CLEARANCES FOR STREET TREES (WHEN TREES ARE PLANTED 1.5M FROM THE CURB):

2M FROM WATER HYDRANTS

2M FROM DRIVEWAYS

2M FROM NEIGHBOURHOOD MAILBOXES

3M FROM HYDRO TRANSFORMERS

5M FROM STREETLIGHTS

15M MINIMUM FROM STREET LINE (STREET INTERSECTION AS MEASURED FROM BACK OF CURB) AND BEHIND THE DAYLIGHT TRIANGLE AS PER THE GEOMETRIC DESIGN STANDARDS FOR ONTARIO HIGHWAYS

18M FROM FACE OF ALL WARNING AND REGULATORY SIGNS

NOTE 3

THE TREE PITS AND PLANTING BEDS FOR ALL TREES AND SHRUBS LOCATED WITHIN 1 METRE OF UNDERGROUND UTILITIES ARE TO BE HAND DUG.

TOWN OF CALEDON					APR'D: C.C.	DATE: APRIL 2000
GENERAL LANDSCAPING NOTES	2	TEXT REVISION, STD103 NOW 700		JAN 18	DRAWN: BJM	SCALE: NTS
	1	STANDARD No. 130 NOW 103		JUNE 08	STANDARD No. 700	
	NO.	REVISION	APR'D	DATE		